

Sterling 144 Zone Assay Data – 2008

Underground Drilling

| | Total Length (ft) | Interval from (ft) | Interval to (ft) | Length (ft) | Gold oz/t | Interval from (m) | Interval to (m) | Length (m) | Gold g/t |
|------------------|----------------------|-----------------------|---------------------|----------------|--------------|----------------------|--------------------|---------------|-------------|
| SU08-1 | 191.0 | 90.0 | 191.0 | 101.0 | 0.054 | 27.43 | 58.22 | 30.78 | 1.84 |
| <i>including</i> | | 110.0 | 120.0 | 10.0 | 0.259 | 33.53 | 36.58 | 3.05 | 8.90 |
| <i>including</i> | | 100.0 | 184.5 | 84.5 | 0.059 | 30.48 | 56.24 | 25.76 | 2.01 |
| SU08-2 | 155.0 | 97.5 | 155.0 | 57.5 | 0.040 | 29.72 | 47.24 | 17.53 | 1.36 |
| <i>including</i> | | 120.0 | 145.0 | 25.0 | 0.074 | 36.58 | 44.20 | 7.62 | 2.55 |
| SU08-3 | 234.0 | 77.7 | 234.0 | 156.3 | 0.032 | 23.68 | 71.32 | 47.64 | 1.09 |
| <i>including</i> | | 82.5 | 109.0 | 26.5 | 0.100 | 25.15 | 33.22 | 8.08 | 3.44 |
| SU08-4 | 255.5 | 99.0 | 255.5 | 156.5 | 0.035 | 30.18 | 77.88 | 47.70 | 1.18 |
| <i>including</i> | | 114.0 | 132.0 | 18.0 | 0.089 | 34.75 | 40.23 | 5.49 | 3.06 |
| <i>including</i> | | 202.0 | 227.0 | 25.0 | 0.060 | 61.57 | 69.19 | 7.62 | 2.04 |
| SU08-5 | 212.0 | 92.0 | 212.0 | 120.0 | 0.021 | 28.04 | 64.62 | 36.58 | 0.70 |
| <i>including</i> | | 113.0 | 118.0 | 5.0 | 0.146 | 34.44 | 35.97 | 1.52 | 5.01 |
| SU08-6 | 295.0 | 76.4 | 295.0 | 218.6 | 0.030 | 23.29 | 89.92 | 66.63 | 1.02 |
| <i>including</i> | | 81.4 | 103.0 | 21.6 | 0.147 | 24.81 | 31.39 | 6.58 | 5.06 |
| SU08-7 | 358.0 | 87.0 | 210.9 | 123.9 | 0.036 | 26.52 | 64.28 | 37.76 | 1.25 |
| <i>including</i> | | 142.5 | 173.0 | 30.5 | 0.129 | 43.43 | 52.73 | 9.30 | 4.43 |
| SU08-8 | 229.0 | 98.5 | 229.0 | 130.5 | 0.058 | 30.02 | 69.80 | 39.78 | 1.98 |
| <i>including</i> | | 113.0 | 176.0 | 63.0 | 0.111 | 34.44 | 53.64 | 19.20 | 3.79 |
| <i>including</i> | | 113.0 | 204.0 | 91.0 | 0.082 | 34.44 | 62.18 | 27.74 | 2.80 |
| SU08-9 | 309.0 | 148.5 | 308.3 | 159.8 | 0.019 | 45.26 | 93.97 | 48.71 | 0.64 |
| <i>including</i> | | 197.0 | 210.2 | 13.2 | 0.060 | 60.05 | 64.07 | 4.02 | 2.07 |
| <i>including</i> | | 158.5 | 303.3 | 144.8 | 0.020 | 48.31 | 92.45 | 44.14 | 0.70 |

:: reported in news release

Sterling 144 Zone Assay Data – 2008

Underground Drilling

| | Total Length (ft) | Interval from (ft) | Interval to (ft) | Length (ft) | Gold oz/t | Interval from (m) | Interval to (m) | Length (m) | Gold g/t |
|------------------|----------------------|-----------------------|---------------------|----------------|--------------|----------------------|--------------------|---------------|-------------|
| SU08-10 | 283.0 | 125.8 | 283.0 | 157.2 | 0.043 | 38.34 | 86.26 | 47.91 | 1.48 |
| <i>including</i> | | 138.0 | 178.0 | 40.0 | 0.095 | 42.06 | 54.25 | 12.19 | 3.26 |
| SU08-11 | 277.5 | 124.0 | 277.5 | 153.5 | 0.139 | 37.80 | 84.58 | 46.79 | 4.78 |
| <i>including</i> | | 203.5 | 211.0 | 7.5 | 0.543 | 62.03 | 64.31 | 2.29 | 18.63 |
| <i>including</i> | | 163.5 | 275.5 | 112.0 | 0.170 | 49.83 | 83.97 | 34.14 | 5.81 |
| <i>including</i> | | 129.0 | 135.0 | 6.0 | 0.157 | 39.32 | 41.15 | 1.83 | 5.37 |
| <i>including</i> | | 129.0 | 275.5 | 146.5 | 0.148 | 39.32 | 83.97 | 44.65 | 5.07 |
| SU08-12 | 109.0 | 0.0 | 88.5 | 88.5 | 0.069 | 0.00 | 26.97 | 26.97 | 2.36 |
| <i>including</i> | | 67.3 | 78.5 | 11.2 | 0.165 | 20.51 | 23.93 | 3.41 | 5.67 |
| <i>including</i> | | 27.3 | 83.5 | 56.2 | 0.092 | 8.32 | 25.45 | 17.13 | 3.16 |
| SU08-13 | 154.0 | 0.0 | 153.0 | 153.0 | 0.047 | 0.00 | 46.63 | 46.63 | 1.60 |
| <i>including</i> | | 10.0 | 35.0 | 25.0 | 0.101 | 3.05 | 10.67 | 7.62 | 3.47 |
| <i>including</i> | | 53.0 | 61.3 | 8.3 | 0.064 | 16.15 | 18.68 | 2.53 | 2.21 |
| SU08-14 | 139.0 | 0.0 | 139.0 | 139.0 | 0.047 | 0.00 | 42.37 | 42.37 | 1.62 |
| <i>including</i> | | 86.5 | 101.5 | 15.0 | 0.103 | 26.37 | 30.94 | 4.57 | 3.53 |
| SU08-15 | 264.0 | 0.0 | 264.0 | 264.0 | 0.065 | 0.00 | 80.47 | 80.47 | 2.25 |
| <i>including</i> | | 10.0 | 48.7 | 38.7 | 0.154 | 3.05 | 14.84 | 11.80 | 5.28 |
| <i>including</i> | | 0.0 | 203.0 | 203.0 | 0.079 | 0.00 | 61.87 | 61.87 | 2.72 |
| SU08-16 | 79.5 | 0.0 | 79.5 | 79.5 | 0.133 | 0.00 | 24.23 | 24.23 | 4.57 |
| <i>including</i> | | 10.0 | 25.0 | 15.0 | 0.302 | 3.05 | 7.62 | 4.57 | 10.36 |
| <i>including</i> | | 10.0 | 55.5 | 45.5 | 0.208 | 3.05 | 16.92 | 13.87 | 7.14 |

:: reported in news release

Sterling 144 Zone Assay Data – 2008

Underground Drilling

| | Total Length (ft) | Interval from (ft) | Interval to (ft) | Length (ft) | Gold oz/t | Interval from (m) | Interval to (m) | Length (m) | Gold g/t |
|------------------|----------------------|-----------------------|---------------------|----------------|--------------|----------------------|--------------------|---------------|-------------|
| SU08-17 | 99.0 | 0.0 | 81.5 | 81.5 | 0.088 | 0.00 | 24.84 | 24.84 | 3.03 |
| <i>including</i> | | 0.0 | 47.0 | 47.0 | 0.148 | 0.00 | 14.33 | 14.33 | 5.08 |
| <i>including</i> | | 19.0 | 24.0 | 5.0 | 0.415 | 5.79 | 7.32 | 1.52 | 14.23 |
| SU08-18 | 327.0 | 82.0 | 327.0 | 245.0 | 0.017 | 24.99 | 99.67 | 74.68 | 0.58 |
| <i>including</i> | | 199.7 | 209.7 | 10.0 | 0.100 | 60.87 | 63.92 | 3.05 | 3.43 |
| <i>including</i> | | 199.7 | 227.5 | 27.8 | 0.061 | 60.87 | 69.34 | 8.47 | 2.10 |
| SU08-19 | 235.0 | 30.0 | 235.0 | 205.0 | 0.046 | 9.14 | 71.63 | 62.48 | 1.56 |
| <i>including</i> | | 101.7 | 170.0 | 68.3 | 0.120 | 31.00 | 51.82 | 20.82 | 4.11 |
| <i>including</i> | | 140.0 | 160.0 | 20.0 | 0.284 | 42.67 | 48.77 | 6.10 | 9.73 |
| SU08-20 | 207.0 | 58.0 | 178.0 | 120.0 | 0.059 | 17.68 | 54.25 | 36.58 | 2.03 |
| <i>including</i> | | 138.0 | 153.0 | 15.0 | 0.252 | 42.06 | 46.63 | 4.57 | 8.64 |
| <i>including</i> | | 102.7 | 159.5 | 56.8 | 0.117 | 31.30 | 48.62 | 17.31 | 4.03 |
| SU08-21 | 287.0 | 78.0 | 287.0 | 209.0 | 0.065 | 23.77 | 87.48 | 63.70 | 2.23 |
| <i>including</i> | | 106.4 | 183.0 | 76.6 | 0.154 | 32.43 | 55.78 | 23.35 | 5.27 |
| <i>including</i> | | 138.0 | 148.0 | 10.0 | 0.266 | 42.06 | 45.11 | 3.05 | 9.14 |
| <i>including</i> | | 168.0 | 183.0 | 15.0 | 0.249 | 51.21 | 55.78 | 4.57 | 8.55 |
| SU08-22 | 292.0 | 123.0 | 270.0 | 147.0 | 0.238 | 37.49 | 82.30 | 44.81 | 8.15 |
| <i>including</i> | | 148.5 | 260.7 | 112.2 | 0.322 | 45.26 | 79.46 | 34.20 | 11.05 |
| <i>including</i> | | 170.0 | 185.0 | 15.0 | 1.006 | 51.82 | 56.39 | 4.57 | 34.49 |
| SU08-23 | 294.0 | 181.3 | 294.0 | 112.7 | 0.026 | 55.26 | 89.61 | 34.35 | 0.89 |
| <i>including</i> | | 206.0 | 221.0 | 15.0 | 0.064 | 62.79 | 67.36 | 4.57 | 2.20 |
| SU08-24 | 333.0 | 205.0 | 333.0 | 128.0 | 0.060 | 62.48 | 101.50 | 39.01 | 2.06 |
| <i>including</i> | | 215.0 | 313.0 | 98.0 | 0.077 | 65.53 | 95.40 | 29.87 | 2.65 |
| <i>including</i> | | 246.5 | 256.5 | 10.0 | 0.145 | 75.13 | 78.18 | 3.05 | 4.96 |

:: reported in news release

Sterling 144 Zone Assay Data – 2008

Underground Drilling

| | Total Length (ft) | Interval from (ft) | Interval to (ft) | Length (ft) | Gold oz/t | Interval from (m) | Interval to (m) | Length (m) | Gold g/t |
|------------------|----------------------|---------------------------|---------------------|----------------|--------------|----------------------|--------------------|---------------|-------------|
| SU08-25 | 253.0 | No significant intercepts | | | | | | | |
| SU08-26 | 374.0 | 156.0 | 374.0 | 218.0 | 0.025 | 47.55 | 114.00 | 66.45 | 0.86 |
| <i>including</i> | | 339.0 | 369.0 | 30.0 | 0.077 | 103.33 | 112.47 | 9.14 | 2.65 |
| SU08-27 | 394.0 | 157.0 | 394.0 | 237.0 | 0.048 | 47.85 | 120.09 | 72.24 | 1.63 |
| <i>including</i> | | 213.3 | 390.0 | 176.7 | 0.063 | 65.01 | 118.87 | 53.86 | 2.16 |
| <i>including</i> | | 344.0 | 374.0 | 30.0 | 0.107 | 104.85 | 114.00 | 9.14 | 3.68 |
| SU08-28 | 454.0 | 41.0 | 454.0 | 413.0 | 0.020 | 12.50 | 138.38 | 125.88 | 0.69 |
| <i>including</i> | | 186.6 | 278.5 | 91.9 | 0.060 | 56.88 | 84.89 | 28.01 | 2.06 |
| <i>including</i> | | 191.5 | 194.5 | 3.0 | 0.125 | 58.37 | 59.28 | 0.91 | 4.29 |
| SU08-29 | 324.0 | 54.0 | 324.0 | 270.0 | 0.007 | 16.46 | 98.76 | 82.30 | 0.23 |
| <i>including</i> | | 269.0 | 304.0 | 35.0 | 0.014 | 81.99 | 92.66 | 10.67 | 0.48 |
| SU08-30 | 379.0 | 43.0 | 379.0 | 336.0 | 0.009 | 13.11 | 115.52 | 102.41 | 0.31 |
| <i>including</i> | | 304.0 | 308.8 | 4.8 | 0.038 | 92.66 | 94.12 | 1.46 | 1.29 |
| SU08-31 | 489.0 | 74.0 | 489.0 | 415.0 | 0.045 | 22.56 | 149.05 | 126.49 | 1.56 |
| <i>including</i> | | 248.0 | 459.0 | 211.0 | 0.071 | 75.59 | 139.90 | 64.31 | 2.44 |
| <i>including</i> | | 248.0 | 273.0 | 25.0 | 0.089 | 75.59 | 83.21 | 7.62 | 3.05 |
| <i>including</i> | | 369.0 | 374.0 | 5.0 | 0.145 | 112.47 | 114.00 | 1.52 | 4.95 |
| <i>including</i> | | 414.0 | 429.0 | 15.0 | 0.128 | 126.19 | 130.76 | 4.57 | 4.39 |

:: reported in news release

Sterling 144 Zone Assay Data – 2008

Underground Drilling

| | Total Length (ft) | Interval from (ft) | Interval to (ft) | Length (ft) | Gold oz/t | Interval from (m) | Interval to (m) | Length (m) | Gold g/t |
|------------------|-------------------------|-----------------------|---------------------|----------------|--------------|----------------------|--------------------|---------------|-------------|
| SU08-32 | 379.0 | 154.0 | 374.0 | 220.0 | 0.037 | 46.94 | 114.00 | 67.06 | 1.27 |
| <i>including</i> | | 339.0 | 354.0 | 15.0 | 0.143 | 103.33 | 107.90 | 4.57 | 4.90 |
| <i>including</i> | | 199.0 | 369.0 | 170.0 | 0.046 | 60.66 | 112.47 | 51.82 | 1.58 |
| SU08-33 | 263.0 | 67.0 | 248.0 | 181.0 | 0.019 | 20.42 | 75.59 | 55.17 | 0.64 |
| <i>including</i> | | 174.0 | 234.0 | 60.0 | 0.047 | 53.04 | 71.32 | 18.29 | 1.61 |
| SU08-34 | 206.0 | 73.0 | 206.0 | 133.0 | 0.007 | 22.25 | 62.79 | 40.54 | 0.24 |
| <i>including</i> | | 173.8 | 187.0 | 13.2 | 0.037 | 52.97 | 57.00 | 4.02 | 1.28 |
| SU08-35 | 344.0 | 183.0 | 344.0 | 161.0 | 0.040 | 55.78 | 104.85 | 49.07 | 1.36 |
| <i>including</i> | | 308.0 | 334.0 | 26.0 | 0.118 | 93.88 | 101.80 | 7.92 | 4.04 |
| <i>including</i> | | 258.0 | 344.0 | 86.0 | 0.061 | 78.64 | 104.85 | 26.21 | 2.10 |
| SU08-36 | 394.0 | 164.0 | 394.0 | 230.0 | 0.025 | 49.99 | 120.09 | 70.10 | 0.87 |
| <i>including</i> | | 219.0 | 229.0 | 10.0 | 0.102 | 66.75 | 69.80 | 3.05 | 3.50 |
| <i>including</i> | | 219.0 | 380.0 | 161.0 | 0.038 | 66.75 | 115.82 | 49.07 | 1.30 |
| SU08-37 | 314.0 | 201.0 | 314.0 | 113.0 | 0.019 | 61.26 | 95.71 | 34.44 | 0.64 |
| <i>including</i> | | 290.0 | 294.0 | 4.0 | 0.126 | 88.39 | 89.61 | 1.22 | 4.32 |
| SU08-38 | 323.0 | 219.0 | 323.0 | 104.0 | 0.002 | 66.75 | 98.45 | 31.70 | 0.08 |
| <i>including</i> | | 318.0 | 323.0 | 5.0 | 0.011 | 96.93 | 98.45 | 1.52 | 0.39 |
| SU08-39 | 334.0 | 221.0 | 334.0 | 113.0 | 0.005 | 67.36 | 101.80 | 34.44 | 0.17 |
| <i>including</i> | | 273.0 | 278.0 | 5.0 | 0.019 | 83.21 | 84.73 | 1.52 | 0.64 |
| SU08-40 | 384.0 | 0.0 | 359.0 | 359.0 | 0.006 | 0.00 | 109.42 | 109.42 | 0.22 |
| <i>including</i> | | 50.0 | 57.4 | 7.4 | 0.127 | 15.24 | 17.50 | 2.26 | 4.35 |
| SU08-41 | 236.0 | 120.0 | 236.0 | 116.0 | 0.013 | 36.58 | 71.93 | 35.36 | 0.43 |
| <i>including</i> | | 131.0 | 159.0 | 28.0 | 0.044 | 39.93 | 48.46 | 8.53 | 1.50 |

:: reported in news release

Sterling 144 Zone Assay Data – 2008

Underground Drilling

| | Total Length (ft) | Interval from (ft) | Interval to (ft) | Length (ft) | Gold oz/t | Interval from (m) | Interval to (m) | Length (m) | Gold g/t |
|------------------|-------------------|--------------------|------------------|-------------|-----------|-------------------|-----------------|------------|----------|
| SU08-42 | 195.0 | 0.0 | 195.0 | 195.0 | 0.030 | 0.00 | 59.44 | 59.44 | 1.01 |
| <i>including</i> | | 93.0 | 113.0 | 20.0 | 0.141 | 28.35 | 34.44 | 6.10 | 4.84 |
| <i>including</i> | | 83.0 | 153.0 | 70.0 | 0.074 | 25.30 | 46.63 | 21.34 | 2.52 |
| SU08-43 | 189.0 | 114.0 | 189.0 | 75.0 | 0.067 | 34.75 | 57.61 | 22.86 | 2.31 |
| <i>including</i> | | 135.0 | 140.0 | 5.0 | 0.360 | 41.15 | 42.67 | 1.52 | 12.36 |
| <i>including</i> | | 135.0 | 154.0 | 19.0 | 0.178 | 41.15 | 46.94 | 5.79 | 6.09 |
| SU08-44 | 234.0 | 0.0 | 234.0 | 234.0 | 0.031 | 0.00 | 71.32 | 71.32 | 1.06 |
| <i>including</i> | | 160.0 | 198.3 | 38.3 | 0.053 | 48.77 | 60.44 | 11.67 | 1.80 |
| <i>including</i> | | 5.0 | 60.0 | 55.0 | 0.041 | 1.52 | 18.29 | 16.76 | 1.40 |
| SU08-45 | 224.0 | 0.0 | 224.0 | 224.0 | 0.054 | 0.00 | 68.28 | 68.28 | 1.86 |
| <i>including</i> | | 45.0 | 50.0 | 5.0 | 0.150 | 13.72 | 15.24 | 1.52 | 5.16 |
| <i>including</i> | | 0.0 | 115.0 | 115.0 | 0.077 | 0.00 | 35.05 | 35.05 | 2.65 |
| SU08-46 | 119.0 | 0.0 | 119.0 | 119.0 | 0.052 | 0.00 | 36.27 | 36.27 | 1.79 |
| <i>including</i> | | 75.0 | 91.0 | 16.0 | 0.109 | 22.86 | 27.74 | 4.88 | 3.72 |
| <i>including</i> | | 50.0 | 111.0 | 61.0 | 0.068 | 15.24 | 33.83 | 18.59 | 2.34 |
| SU08-47 | 160.5 | 47.0 | 161.0 | 114.0 | 0.156 | 14.33 | 49.07 | 34.75 | 5.36 |
| <i>including</i> | | 108.0 | 113.0 | 5.0 | 0.424 | 32.92 | 34.44 | 1.52 | 14.55 |
| <i>including</i> | | 73.0 | 118.0 | 45.0 | 0.256 | 22.25 | 35.97 | 13.72 | 8.79 |
| <i>including</i> | | 73.0 | 161.0 | 88.0 | 0.197 | 22.25 | 49.07 | 26.82 | 6.76 |
| SU08-48 | 199.0 | 42.0 | 199.0 | 157.0 | 0.166 | 12.80 | 60.66 | 47.85 | 5.70 |
| <i>including</i> | | 82.0 | 92.0 | 10.0 | 0.621 | 24.99 | 28.04 | 3.05 | 21.29 |
| <i>including</i> | | 72.0 | 184.0 | 112.0 | 0.210 | 21.95 | 56.08 | 34.14 | 7.20 |
| SU08-49 | | | | | | | | | |

Hole Abandoned

:: reported in news release

Sterling 144 Zone Assay Data – 2008

Underground Drilling

| | Total Length (ft) | Interval from (ft) | Interval to (ft) | Length (ft) | Gold oz/t | Interval from (m) | Interval to (m) | Length (m) | Gold g/t |
|------------------|----------------------------------|-------------------------------|-----------------------------|------------------------|----------------------|------------------------------|----------------------------|-----------------------|---------------------|
| SU08-50 | 262.5 | 88.0 | 262.5 | 174.5 | 0.082 | 26.82 | 80.01 | 53.19 | 2.80 |
| <i>including</i> | | 113.0 | 128.0 | 15.0 | 0.432 | 34.44 | 39.01 | 4.57 | 14.82 |
| <i>including</i> | | 113.0 | 153.0 | 40.0 | 0.223 | 34.44 | 46.63 | 12.19 | 7.64 |
| <i>including</i> | | 182.0 | 242.0 | 60.0 | 0.081 | 55.47 | 73.76 | 18.29 | 2.79 |
| SU08-51 | 145.0 | 89.0 | 145.0 | 56.0 | 0.023 | 27.13 | 44.20 | 17.07 | 0.78 |
| <i>including</i> | | 122.5 | 127.5 | 5.0 | 0.093 | 37.34 | 38.86 | 1.52 | 3.18 |
| SU08-52 | 224.0 | 72.0 | 224.0 | 152.0 | 0.013 | 21.95 | 68.28 | 46.33 | 0.43 |
| <i>including</i> | | 98.5 | 103.0 | 4.5 | 0.111 | 30.02 | 31.39 | 1.37 | 3.81 |
| <i>including</i> | | 163.0 | 168.0 | 5.0 | 0.040 | 49.68 | 51.21 | 1.52 | 1.36 |

:: reported in news release

Sterling 144 Zone Assay Data – 2008

Surface Drilling

| | Total Length (ft) | Interval from (ft) | Interval to (ft) | Length (ft) | Gold oz/t | Interval from (m) | Interval to (m) | Length (m) | Gold g/t |
|----------|----------------------|-----------------------|---------------------|----------------|--------------|----------------------|--------------------|---------------|-------------|
| MG08-01 | 1435.0 | 850.0 | 1435.0 | 585.0 | 0.001 | 259.08 | 437.39 | 178.31 | 0.02 |
| incl | | 1165.0 | 1185.0 | 20.0 | 0.003 | 355.09 | 361.19 | 6.10 | 0.10 |
| incl | | 1280.0 | 1300.0 | 20.0 | 0.003 | 390.14 | 396.24 | 6.10 | 0.11 |
| incl | | 1125.0 | 1240.0 | 115.0 | 0.002 | 342.90 | 377.95 | 35.05 | 0.05 |
| incl | | 1265.0 | 1370.0 | 105.0 | 0.001 | 385.57 | 417.58 | 32.00 | 0.05 |
| FC08-01A | 1035.0 | 245.0 | 320.0 | 75.0 | 0.004 | 74.68 | 97.54 | 22.86 | 0.15 |
| incl | | 810.0 | 1035.0 | 225.0 | 0.001 | 246.89 | 315.47 | 68.58 | 0.03 |
| incl | | 255.0 | 265.0 | 10.0 | 0.015 | 77.72 | 80.77 | 3.05 | 0.53 |
| FC08-02 | 1350.0 | 940.0 | 1350.0 | 410.0 | 0.003 | 286.51 | 411.48 | 124.97 | 0.09 |
| incl | | 940.0 | 950.0 | 10.0 | 0.027 | 286.51 | 289.56 | 3.05 | 0.94 |
| incl | | 940.0 | 1035.0 | 95.0 | 0.004 | 286.51 | 315.47 | 28.96 | 0.15 |

:: reported in news release