

Mount Polley 2010/2011 Drilling

C2 Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
C210-82	270	-60	300.8	NSI				
C210-83	270	-60	468.5	240.0	312.5	72.5	0.24	0.58
including			468.5	275.0	287.5	12.5	0.29	2.37
C210-84	270	-60	495.9	50.7	112.5	61.9	0.22	0.30
and				405.0	437.5	32.5	0.53	0.83
C210-85	90	-60	279.5	9.1	40.0	30.9	0.17	0.23
and				95.0	132.5	37.5	0.21	0.19
and				185.0	197.5	12.5	0.28	0.18
and				210.0	265.0	55.0	0.29	0.46
May 2011								
C211-86	90	-60	409.4	185.0	212.5	27.5	0.81	1.01
C211-87	90	-60	572.1	218.5	513.3	294.8	0.31	0.37
including				221.6	252.5	30.9	1.04	1.19
C211-88	270	-60	380.1	NSI				
C211-89	270	-60	569.1	22.5	47.5	25.0	0.50	0.54
and				76.5	87.5	11.0	0.28	0.22
and				180.0	192.5	12.5	0.23	0.21
and				207.5	222.5	15.0	0.23	0.20
and				274.8	287.5	12.7	0.27	0.25
and				320.0	390.7	70.7	0.23	0.29
and				417.5	430.0	12.5	0.35	0.36
and				562.5	569.1	6.6	0.39	1.23
C211-90	90	-60	355.7	177.5	242.5	65.0	0.24	0.32
and				290.0	320.0	30.0	0.21	0.29
C211-91	90	-60	383.1	175.0	197.5	22.5	0.21	0.34
and				222.5	235.0	12.5	0.24	0.40
C211-92	90	-60	401.4	5.2	17.5	12.3	0.63	0.65
and				37.5	52.5	15.0	0.18	0.28
and				110.0	127.5	17.5	0.23	0.25
and				150.0	257.5	107.5	0.25	0.37
C211-93	270	-60	434.9	12.5	47.5	35.0	0.24	0.30
and				92.5	102.5	10.0	0.30	0.29
and				137.5	165.0	27.5	0.24	0.23
and				185.0	291.7	106.7	0.24	0.40
and				347.5	357.5	10.0	0.24	0.25
C211-94	270	-60	611.7	17.4	117.5	100.1	0.40	0.56
including				72.5	100.0	27.5	0.70	1.28
and				262.5	508.1	245.6	0.20	0.26
and				587.5	599.8	12.3	0.34	0.60
Aug 2011								
C211-95	270	-60	592.5	45.0	77.5	32.5	0.19	0.23
and				190.0	235.0	45.0	0.23	0.54
and				294.8	506.5	211.7	0.30	0.43
including				490.3	497.5	7.2	0.74	2.58
C211-96	90	-60	578.2	3.1	60.0	57.0	0.18	0.23
and				77.5	307.5	230.0	0.27	0.30
including				290.0	305.0	15.0	1.11	1.19
and				375.0	445.0	70.0	0.19	0.28

Mount Polley 2010/2011 Drilling

C2 Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
C211-97	270	-60	524.9	287.5	404.5	117.0	0.69	1.17
including				362.5	397.5	35.0	1.33	3.02
C211-98	90	-60	325.2	NSI				
C211-99	90	-60	397.8	212.5	330.0	117.5	0.19	0.20
C211-100	270	-60	529.4	182.5	446.8	264.3	0.31	0.35
including				382.5	446.8	64.3	0.72	0.99
C211-101	270	-60	361.8	163.7	332.5	168.8	0.23	0.35
including				297.5	332.0	34.5	0.54	0.95
C211-102	90	-60	465.4	85.0	270.0	185.0	0.28	0.46
including				85.0	112.5	27.5	0.89	1.59
C211-103	90	-60	398.4	210.0	302.5	92.5	0.17	0.19
C211-104	270	-67	342.6	105.0	127.5	22.5	0.22	0.18
and				221.6	233.8	12.2	0.22	0.13
C211-105	90	-60	444.1	11.1	32.5	21.5	0.21	0.21
and				55.0	110.0	55.0	0.20	0.14
and				170.0	195.0	25.0	0.16	0.13
C211-106	90	-60	532.5	360.0	395.0	35.0	0.22	0.25
and				522.5	532.5	10.0	0.16	0.28
C211-107	270	-60	465.4	157.5	167.5	10.0	0.28	0.13
and				220.0	280.0	60.0	0.15	0.16
and				316.8	327.5	10.7	0.22	0.27
and				362.5	385.0	22.5	0.25	0.17
C211-108	270	-60	438.0	NSI				
C211-109	90	-60	313.0	NSI				

| Feb 2012 |

Mount Polley 2010/2011 Drilling

Cariboo Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
CB11-01	320	-60	647.3	195.0	284.0	89.0	0.23	0.26
and				460.0	470.0	10.0	0.34	0.36
and				492.5	502.5	10.0	0.20	0.27
CB11-02	320	-60	681.8	45.0	55.0	10.0	1.52	2.21
and				242.5	260.0	17.5	0.23	0.38
and				277.5	342.5	65.0	0.21	0.28
and				615.3	677.5	62.2	0.25	0.35
CB11-03	320	-60	623.9	177.5	205.0	27.5	0.17	0.27
and				257.5	325.0	67.5	0.18	0.20
CB11-04	270	-45	1175.0	13.8	257.5	243.7	0.21	0.21
and				309.4	345.8	36.4	0.43	0.39
and				560.0	622.5	62.5	0.27	0.30
and				635.0	647.5	12.5	0.30	0.41
and				732.5	760.0	27.5	0.20	0.33
and				852.5	885.0	32.5	0.15	0.36
and				922.0	1137.5	215.5	0.23	0.21
CB11-04	270	-50	835.0	659.4	702.5	43.1	0.26	0.64
CB11-05	270	-50	1083.9	280.0	370.0	90.0	0.16	0.15
and				430.0	470.0	40.0	0.16	0.22
and				655.0	705.0	50.0	0.25	0.59
CB11-06	270	-50	498.4 NSI					

| Feb 2012 |

Mount Polley 2010/2011 Drilling

Junction Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
JZ10-45	270	-60	200.3	NSI				
JZ10-46	270	-60	249.0	139.9	249.0	109.1	0.19	0.28
including				139.9	180.0	40.1	0.25	0.51
JZ10-47	270	-60	394.4	365.0	392.5	27.5	0.33	0.13
May 2010								
JZ10-48	270	-60	507.5	259.1	347.5	88.4	0.23	0.28
JZ10-49	270	-60	318.5	100.0	130.0	30.0	0.23	0.41
JZ10-50	270	-60	245.4	70.0	107.2	37.2	0.19	0.33
JZ10-51	270	-60	211.8	NSI				
JZ10-52	270	-60	449.6	160.0	307.5	147.5	0.21	0.21
JZ10-53	270	-60	248.7	140.0	150.0	10.0	0.24	0.37
JZ10-54	270	-60	263.7	5.0	17.5	12.5	0.24	0.14
JZ10-55	270	-60	297.2	92.5	127.5	35.0	0.30	0.42
and				252.5	272.5	20.0	0.39	0.15
JZ10-56	270	-60	316.1	20.0	42.5	22.5	0.23	0.20
and				185.0	197.5	12.5	0.27	0.16
JZ10-57	90	-60	245.4	117.5	135.0	17.5	0.26	0.65
JZ10-58	270	-60	379.8	20.0	32.5	12.5	0.26	0.26
and				132.5	147.5	15.0	0.35	0.11
and				262.5	287.5	25.0	0.41	0.23
and				297.5	327.5	30.0	0.39	0.18
JZ10-59	270	-60	425.2	NSI				
JZ10-60	270	-60	269.8	160.0	183.6	23.6	0.14	0.28
JZ10-61	270	-60	495.6	382.4	451.1	68.7	0.26	0.30
JZ10-62	270	-60	313.0	NSI				
Jul 2010								
JZ-11-63	270	-60	68.6	lost hole				
JZ-11-63A	270	-60	85.3	lost hole				
JZ-11-64	270	-60	310.0	40.0	52.5	12.5	0.20	0.19
and				237.5	265.0	27.5	0.31	0.15
and				285.0	295.0	10.0	0.23	0.08
JZ-11-65	270	-60	340.5	NSI				
JZ-11-66	270	-60	182.0	NSI				
JZ-11-67	270	-60	282.6	NSI				

|Feb 2012|

Mount Polley 2010/2011 Drilling

Skid Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
JC11-02	60	-50	380.1	47.5	60.0	12.5	0.30	0.15
JC11-03	60	-50	334.4	NSI				
JC11-04	240	-50	375.0	22.5	35.0	12.5	0.38	0.23
and				157.1	177.5	20.4	0.44	0.05
JC11-05	240	-50	473.2	15.2	50.0	34.8	0.50	0.19

| Feb 2012 |

Mount Polley Drilling

WX Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
WX10-03	270	-70	380.1	50.0	210.0	160.0	0.24	0.37
including				158.3	172.5	14.2	0.52	1.25
and				345.0	352.5	7.5	0.33	1.86
May 2010								
WX10-04			413.3	150.0	257.5	107.5	0.16	0.19
and	90	-60		279.1	360.0	80.9	0.23	0.37
including				332.5	360.0	27.5	0.35	0.58
WX10-05	270	-60	331.0	3.1	155.0	151.9	0.16	0.35
including				20.0	80.0	60.0	0.22	0.58
and				222.5	250.0	27.5	0.12	0.28
WX10-06	270	-70	450.2	97.5	287.5	190.0	0.53	0.86
including				192.4	282.5	90.1	0.90	1.59
including				242.5	282.5	40.0	1.30	2.46
WX10-07	270	-70	418.4	7.5	45.0	37.5	0.20	0.15
and				70.0	178.3	108.3	0.22	0.21
including				145.0	165.0	20.0	0.44	0.53
WX10-08	90	-60	552.6	87.5	143.1	55.6	0.23	0.35
and				190.0	212.5	22.5	0.10	0.23
and				225.0	509.2	284.2	0.30	0.55
including				287.5	329.7	42.2	0.54	0.99
including				360.0	372.5	12.5	0.50	1.34
including				420.0	495.0	75.0	0.48	0.87
Jul 2010								
WX10-09	90	-60	666.6	231.5	338.7	107.1	0.44	0.80
including				255.0	312.9	57.9	0.58	1.16
including				286.8	312.9	26.1	0.87	1.79
and				366.0	387.5	21.5	0.27	0.80
and				410.0	425.0	15.0	0.27	0.43
and				435.0	510.0	75.0	0.37	0.51
and				572.5	583.7	11.2	0.34	0.98
WX10-10	270	-70	578.8	67.5	97.5	30.0	0.12	0.29
and				147.5	292.5	145.0	0.13	0.25
and				417.5	430.0	12.5	0.14	0.37
and				550.0	560.0	10.0	0.21	0.40
WX10-11	270	-70	721.5	17.1	85.0	67.9	0.56	0.59
and				162.5	180.0	17.5	0.35	0.47
and				205.0	220.0	15.0	0.63	1.34
and				257.5	267.5	10.0	0.22	0.83
and				285.0	337.5	52.5	0.31	0.67
and				529.5	598.5	69.0	0.40	0.85
including				529.5	550.0	20.5	0.55	1.24
and				580.2	597.5	17.3	0.73	1.63
WX10-12	270	-70	517.3	10.0	47.5	37.5	0.12	0.42
and				67.5	77.5	10.0	0.13	0.41
and				245.0	277.5	32.5	0.08	0.35
and				310.0	322.5	12.5	0.25	0.98

Mount Polley Drilling

WX Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
WX10-13	270	-70	633.1	35.0	130.0	95.0	0.34	0.48
including				95.0	105.0	10.0	1.10	1.88
and				262.5	312.5	50.0	0.33	0.54
and				573.5	590.0	16.5	0.51	1.55
WX10-14	270	-70	601.1	195.0	220.0	25.0	0.16	0.33
and				377.5	406.7	29.2	0.22	0.34
WX10-15	270	-70	465.4	267.5	367.5	100.0	0.34	0.96
including				317.5	335.3	17.8	0.73	2.47
WX10-16	90	-60	532.5	NSI				
WX10-17	90	-60	633.1	NSI				
WX10-18	270	-70	523.3	25.0	65.5	40.5	0.70	0.50
and				87.5	107.5	20.0	0.29	0.39
and				155.0	182.5	27.5	0.22	0.17
and				242.5	251.0	8.5	0.60	1.37
and				265.0	350.0	85.0	0.27	0.40
including				305.0	325.0	20.0	0.41	0.81
WX10-19	270	-70	72.5	15.2	55.0	39.8	0.18	0.19
WX10-20	90	-60	490.7	35.0	50.0	15.0	0.27	0.10
and				252.5	280.0	27.5	0.22	0.32
WX10-21	90	-60	479.9	365.0	375.0	10.0	0.36	0.15
WX10-22	270	-70	672.7	272.5	300.0	27.5	0.35	0.36
and				330.0	337.5	7.5	0.29	0.80
and				350.0	507.5	157.5	0.35	0.50
including				440.0	452.5	12.5	0.70	1.25
and				580.1	592.5	12.4	0.42	0.67
WX10-23	270	-70	569.1	100.0	115.0	15.0	0.37	0.34
and				132.5	142.5	10.0	0.38	0.68
and				277.5	295.0	17.5	0.22	0.52
and				340.0	492.5	152.5	0.52	0.82
including				407.5	492.5	85.0	0.64	1.02
WX10-24	270	-70	474.6	25.0	125.0	100.0	0.17	0.25
and				170.0	312.5	142.5	0.24	0.54
WX10-25	270	-70	300.8	88.3	112.5	24.2	0.15	0.30
WX10-26	90	-60	547.1	NSI				
WX10-27	90	-60	620.9	50.0	125.0	75.0	0.12	0.46
and				165.0	295.0	130.0	0.45	1.21
and				475.0	500.0	25.0	0.33	0.62
and				555.0	607.5	52.5	0.17	0.34
Oct 2010								
WX10-28	270	-70	602.6	267.7	307.5	39.8	0.42	0.46
WX10-29	270	-70	455.1	217.5	235.0	17.5	0.31	0.41
WX10-30	90	-60	556.9	17.5	37.5	20.0	0.14	0.34
WX10-31	90	-60	694.2	4.3	37.5	33.2	0.18	0.37
and				355.0	488.5	133.5	0.23	0.28
including				397.5	430.0	32.5	0.35	0.45
and				545.0	570.0	25.0	0.35	0.50

Mount Polley Drilling

WX Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
including				545.0	555.0	10.0	0.51	0.74
WX10-32	85	-60	559.9	167.5	237.5	70.0	0.60	1.38
including				200.0	210.0	10.0	1.14	3.64
WX10-33	270	-70	628.6	145.0	157.5	12.5	0.50	0.98
and				292.5	310.0	17.5	0.35	0.94
and				320.0	340.0	20.0	0.14	0.41
and				417.5	457.5	40.0	0.17	0.25
WX10-34	90	-60	590.4	NSI				
WX10-35	90	-60	819.0	247.5	307.5	60.0	0.25	0.28
and				602.5	647.5	45.0	0.28	0.19
and				702.5	812.5	110.0	0.25	0.22
WX10-36	270	-70	822.1	32.5	45.0	12.5	0.32	0.20
and				175.0	210.0	35.0	0.21	0.44
and				610.0	680.0	70.0	0.38	0.39
and				735.0	750.0	15.0	0.38	0.33
WX10-37	90	-60	730.6	422.5	682.5	260.0	0.29	0.43
including				422.5	455.0	32.5	0.25	0.78
including				472.5	482.0	9.5	0.44	0.71
including				495.0	520.0	25.0	0.76	0.98
WX10-38	90	-60	605.6	60.0	522.5	462.5	0.29	0.60
including				297.5	322.5	25.0	1.02	2.33
including				347.5	420.0	72.5	0.53	1.44
WX10-39	270	-70	761.1	62.5	87.5	25.0	0.12	0.51
and				529.8	555.0	25.2	0.56	0.19
WX10-40	270	-70	812.9	182.5	280.0	97.5	0.44	0.54
including				205.0	215.0	10.0	1.23	1.83
and				590.0	705.0	115.0	0.30	0.62
including				677.5	697.5	20.0	0.38	1.54
WX10-41	270	-70	837.3	12.2	22.5	10.3	0.20	0.28
and				295.0	307.5	12.5	0.19	0.49
and				492.5	510.0	17.5	0.17	0.28
and				528.2	545.0	16.8	0.20	0.36
and				557.5	687.5	130.0	0.30	0.40
including				589.5	605.0	15.5	0.50	1.14
and				740.0	750.0	10.0	0.31	0.72
and				765.0	777.5	12.5	0.20	0.20
WX10-42	270	-70	771.5	45.0	55.0	10.0	0.35	0.19
and				225.0	315.0	90.0	0.63	1.18
including				232.5	245.0	12.5	0.77	1.40
including				252.4	269.9	17.5	1.53	2.82
and				437.5	447.5	10.0	0.19	0.29
and				610.0	727.1	117.1	0.14	0.50
including				685.0	707.5	22.5	0.22	1.27
WX10-43	90	-60	846.4	167.5	177.5	10.0	0.13	0.44
and				237.5	255.0	17.5	0.14	0.82
and				375.0	395.0	20.0	0.28	0.20

Mount Polley Drilling

WX Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
and				585.0	752.5	167.5	0.21	0.47
including				727.5	745.0	17.5	0.48	1.37
WX10-44	90	-60	749.4	257.5	327.5	70.0	0.26	0.32
and				612.5	628.8	16.3	0.30	1.12
and				650.0	660.0	10.0	0.13	0.38
and				710.0	725.0	15.0	0.11	0.34
WX11-45	270	-60	687.9	17.5	49.0	31.5	0.21	0.29
and				75.0	147.5	72.5	0.10	0.25
and				472.5	535.0	62.5	0.21	0.20
WX11-46	270	-60	825.1	467.1	505.0	37.9	0.31	0.38
and				542.5	772.5	230.0	0.26	0.26
including				595.0	632.8	37.8	0.44	0.46
WX11-47	90	-70	514.2	160.0	252.5	92.5	0.28	0.36
including				215.3	235.0	19.7	0.41	0.79
WX11-48	90	-70	355.7	65.0	82.5	17.5	0.25	0.20
and				167.5	217.5	50.0	0.26	0.33
WX11-49	90	-70	510.2	259.6	467.5	207.9	0.16	0.44
including				300.0	337.5	37.5	0.21	1.18
WX11-50	270	-60	630.0	397.5	457.5	60.0	0.22	0.19
and				520.0	545.0	25.0	0.32	0.39
WX11-51	90	-70	628.5	285.8	327.5	41.7	0.36	0.74
and				417.5	505.0	87.5	0.28	0.39
and				542.5	565.0	22.5	0.19	0.33
WX11-52	90	-70	194.2	35.0	105.3	70.3	0.19	0.23
and				171.9	192.5	20.6	0.29	0.36
WX11-53	270	-60	721.5	217.5	305.0	87.5	0.11	0.37
and				592.5	630.0	37.5	0.18	0.34
WX11-54	270	-60	590.4	435.0	445.0	10.0	0.30	0.18
and				460.0	590.4	130.4	0.22	0.18
WX11-55	90	-70	663.6	542.5	555.0	12.5	0.41	0.61
and				589.7	597.5	7.8	0.48	0.77
								May 2011
WX11-56	90	-60	243.1	NSI				
WX11-57	85	-60	566.0	17.5	32.5	15.0	0.34	0.31
and				147.5	160.0	12.5	0.12	0.51
WX11-58	270	-70	438.0	17.5	40.0	22.5	0.19	0.83
and				52.5	65.0	12.5	0.15	0.30
and				390.0	405.0	15.0	0.29	0.17
WX11-59	270	-70	581.3	15.0	38.0	23.0	0.15	0.34
and				205.0	215.0	10.0	0.10	0.40
and				404.3	419.5	15.2	0.22	0.18
and				469.8	537.5	67.7	0.35	0.24
WX11-60	90	-60	659.3	90.0	110.0	20.0	0.10	0.38
and				645.0	659.3	14.3	0.15	0.17
WX11-61	90	-60	630.6	80.0	389.7	309.7	0.20	0.45
including				230.2	262.5	32.3	1.00	1.47

Mount Polley Drilling

WX Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
including				490.0	535.0	45.0	0.21	0.24
WX11-62	270	-70	328.3	80.0	220.0	140.0	0.12	0.31
and				285.0	317.5	32.5	0.14	0.34
WX11-63	270	-70	364.8	45.0	172.5	127.5	0.17	0.59
WX11-64	270	-70	386.2	45.0	90.0	45.0	0.17	0.38
and				235.0	280.0	45.0	0.14	0.89
including				270.0	280.0	10.0	0.30	2.46
and				325.0	335.0	10.0	0.37	1.40
WX11-65	270	-70	270.6	12.5	40.0	27.5	0.19	0.42
WX11-66	270	-70	605.6	96.6	112.5	15.9	0.22	0.17
and				237.5	260.0	22.5	0.19	0.26
and				407.5	432.5	25.0	0.16	0.26
WX11-67	90	-60	620.9	250.0	295.0	45.0	0.20	0.23
and				570.0	584.2	14.2	0.27	0.23
WX11-68	270	-70	133.2	35.0	94.6	59.6	0.35	0.31
WX11-69	90	-60	435.0	227.5	292.5	65.0	0.23	0.12
and				335.0	356.7	21.7	0.24	0.24
WX11-70	270	-70	657.5	12.2	102.9	90.7	0.29	0.29
including				77.5	97.5	20.0	0.56	0.74
and				545.0	565.0	20.0	0.19	0.68
and				600.0	624.3	24.3	0.23	0.57
WX11-71	270	-70	547.7	20.0	162.5	142.5	0.29	0.32
and				235.0	245.0	10.0	0.26	0.34
and				475.0	485.0	10.0	0.12	0.32
WX11-72	270	-70	623.9	35.0	44.6	9.6	0.16	0.25
and				242.5	262.5	20.0	0.23	0.20
and				332.5	392.5	60.0	0.32	0.40

| Aug 2011 |

Mount Polley 2010/2011 Drilling

WX Zone - cubex drilling

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
WX-700000	0	-90	42.0	6.0	36.0	30.0	0.10	0.45
WX-750000	0	-90	42.0	0.0	42.0	42.0	0.13	0.28
WX-780950	0	-90	42.0	0.0	24.0	24.0	0.16	1.11
WX-800000	0	-90	42.0	6.0	36.0	30.0	0.11	0.66
WX-800050	0	-90	42.0	NSI				
WX-800900	0	-90	42.0	6.0	42.0	36.0	0.19	0.24
WX-850000	0	-90	42.0	6.0	24.0	18.0	0.19	0.36
WX-850050	0	-90	42.0	NSI				
WX-850950	0	-90	42.0	0.0	12.0	12.0	0.17	0.70
WX-900050	0	-90	42.0	0.0	42.0	42.0	0.50	0.58
WX-900800	0	-90	42.0	30.0	42.0	12.0	0.31	0.19
WX-950774	0	-90	42.0	30.0	42.0	12.0	0.46	0.09
WX-950800	0	-90	42.0	12.0	36.0	24.0	0.62	0.70
WX-995775	0	-90	42.0	NSI				

| Mar 2011 |

Mount Polley 2010/2011 Drilling

Boundary Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t	
				from	to				
ND10-101	0	-90	480.7	320.0	397.5	77.5	0.34	0.24	
and				445.0	472.3	27.3	0.50	0.21	
ND10-102	0	-90	395.3	210.0	321.4	111.4	0.97	0.70	
including				210.0	220.4	10.3	1.51	1.64	
including				290.0	321.4	31.4	2.33	1.46	
WB10-255	264	-8	601.7	NSI					
							May 2010		
ND10-103	270	-60	212.4	107.5	170.0	62.5	0.49	0.13	
including				109.7	126.9	17.2	1.02	0.28	
ND10-104	270	-60	297.8	NSI					
ND10-105	90	-60	84.4	5.2	20.0	14.8	0.35	0.08	
ND10-106	90	-60	252.1	27.5	38.0	10.5	0.44	0.07	
ND10-107	90	-60	180.4	10.0	22.5	12.5	1.19	0.34	
ND10-108	90	-60	235.3	NSI					
ND10-109	90	-60	155.8	25.0	35.0	10.0	0.43	0.07	
and				62.5	74.7	12.2	1.30	0.29	
ND10-110	90	-60	105.8	62.5	75.0	12.5	0.38	0.05	
ND10-111	270	-60	154.5	NSI					
ND10-112	270	-60	133.2	97.6	117.5	19.9	0.39	0.08	
ND10-113	90	-60	163.7	NSI					
ND10-114	270	-60	124.1	NSI					
ND10-115	270	-60	96.6	NSI					
ND10-116	270	-60	93.6	32.5	40.0	7.5	0.43	0.30	
ND10-117	270	-60	118.0	3.1	17.5	14.4	0.86	0.45	
ND10-118	90	-60	96.0	NSI					
ND10-119	90	-60	328.2	23.7	32.6	8.9	0.90	0.33	
ND10-120	270	-60	135.6	32.5	38.9	6.4	0.40	0.10	
and				65.0	72.5	7.5	0.39	0.06	
ND10-121	270	-60	153.3	55.0	66.9	11.9	0.92	0.17	
ND11-122	270	-60	151.5	NSI					
ND11-123	90	-60	105.8	3.1	15.0	11.9	1.39	0.48	
ND11-124	90	-60	114.9	25.0	35.0	10.0	0.57	0.33	
ND11-125	270	-60	111.9	NSI					
ND11-126	90	-60	145.4	99.4	130.0	30.6	0.23	0.12	
ND11-127	90	-60	160.6	NSI					
ND11-128	90	-60	99.7	27.5	37.5	10.0	0.33	0.17	
ND11-129	90	-60	145.4	NSI					
ND11-130	90	-60	231.9	NSI					
ND11-131	90	-60	145.4	110.0	125.0	15.0	0.33	0.07	
ND11-132	90	-60	84.4	55.0	65.0	10.0	0.74	0.20	
ND11-133	90	-60	106.7	NSI					
ND11-134	270	-60	105.8	22.5	32.5	10.0	2.04	0.66	
ND11-135	270	-60	172.8	NSI					
ND11-136	90	-60	93.6	6.1	40.0	33.9	0.40	0.09	
ND11-137	90	-60	172.8	NSI					

Mount Polley 2010/2011 Drilling

Boundary Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
ND11-138	90	-60	156.1	72.5	90.0	17.5	0.38	0.11
ND11-139	90	-60	197.2	NSI				
ND11-140	90	-60	203.3	122.5	135.0	12.5	0.50	0.09
ND11-141	90	-60	154.3	50.4	57.5	7.2	2.24	1.65
ND11-142	90	-60	151.5	20.0	30.0	10.0	0.48	0.11
ND11-143	270	-60	155.5	NSI				
ND11-144	90	-60	404.5	NSI				
ND11-145	0	-65	136.2	90.6	102.1	11.5	0.28	0.44

| May 2011 |

Mount Polley 2010/2011 Drilling

Boundary Zone Underground

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t	Silver ppm	
				from	to					
NDU11-146	222	-40.0	76.8	32.5	35.5	3.0	0.68	0.78	4.13	
and				40.0	49.6	9.6	2.04	1.26	13.03	
NDU11-147	222	-20.0	66.1	33.2	37.5	4.3	0.66	0.77	3.09	
NDU11-148	226	-39.0	145.1	86.7	101.5	14.8	1.45	0.59	9.80	
including				86.7	92.7	6.0	2.68	1.19	13.13	
and				110.8	115.0	4.2	1.18	0.39	5.48	
NDU11-149	226	-24.0	145.4	82.5	98.5	16.0	2.78	1.02	22.52	
including				88.9	98.5	9.5	4.23	1.51	35.26	
NDU11-150	226	-9.0	118.0	62.3	80.0	17.7	2.16	0.96	9.51	
NDU11-151	226	5.5	139.3	60.0	76.8	16.8	1.50	1.63	12.14	
including				73.1	76.8	3.7	3.91	4.44	34.45	
and				87.5	95.9	8.4	0.41	0.26	1.98	
and				117.0	124.7	7.7	0.48	0.41	2.13	
NDU11-152	226	20.0	188.1	100.0	175.5	75.5	0.65	0.49	3.02	
including				134.9	143.8	8.9	1.33	0.92	5.40	
including				157.5	175.5	18.0	1.27	0.91	5.49	
NDU11-153	226	39.0	166.7	40.0	45.0	5.0	1.14	1.69	5.75	
and				89.6	93.5	3.9	0.76	0.98	3.77	
NDU11-154	212	-39.0	154.5	70.3	97.5	27.2	1.49	1.17	7.91	
including				80.3	97.5	17.2	2.06	1.72	11.32	
and				104.4	109.0	4.6	1.55	0.81	7.74	
NDU11-155	212	-24.0	151.5	70.0	100.0	30.0	0.66	0.92	3.75	
including				77.6	87.5	9.9	1.24	2.34	7.98	
NDU11-156	212	-9.0	166.7	65.0	92.4	27.4	0.37	0.39	1.52	
NDU11-157	212	5.5	157.6	80.0	103.4	23.4	0.45	0.61	1.96	
including				80.0	87.5	7.5	1.08	1.54	4.13	
and				143.1	157.6	14.5	0.50	0.27	1.62	
NDU11-158	212	20.0	130.2	40.0	44.5	4.5	2.28	3.21	12.22	
and				63.1	84.6	21.5	1.08	2.05	4.92	
NDU11-159	222	0.0	133.8	27.8	46.4	18.6	2.26	1.64	9.01	
NDU11-160	222	20.0	153.6	25.0	52.5	27.5	2.56	1.68	14.59	
including				40.0	50.0	10.0	4.52	3.32	30.13	
NDU11-161	222	40.0	127.4	32.2	48.3	16.0	2.46	1.26	15.76	
NDU11-162	222	-60.0	109.7	NSI						
May 2011										
NDU11-163	242	-3.0	154.8	30.0	43.2	13.2	1.23	1.21	6.40	
NDU11-164	242	12.0	127.1	32.5	39.0	6.5	0.73	1.13	3.72	
NDU11-165	210	-60.0	148.4	62.7	74.8	12.1	1.23	0.70	5.04	
NDU11-166	210	-40.0	139.6	42.1	71.6	29.5	1.55	1.00	13.86	
including				45.0	52.5	7.5	2.30	0.91	22.33	
including				62.5	70.0	7.5	3.35	2.82	30.10	
NDU11-167	210	-20.0	154.9	15.0	47.5	32.5	0.73	0.38	3.54	
including				15.0	22.5	7.5	1.17	0.69	4.65	
and				35.6	44.8	9.3	1.29	0.60	7.09	
NDU11-168	210	0.0	154.8	26.6	47.5	20.9	2.33	1.16	9.21	
NDU11-169	210	20.0	170.1	27.5	50.2	22.7	2.52	1.19	24.05	
including				30.0	40.0	10.0	3.75	1.67	44.17	
NDU11-170	210	40.0	154.5	29.9	37.5	7.6	1.40	0.91	6.86	
and				85.3	105.0	19.8	1.62	1.19	5.20	
NDU11-171	173	-31.0	167.0	100.0	112.5	12.5	2.73	1.55	21.00	
NDU11-172	160	-9.0	124.4	107.7	110.9	3.3	2.16	1.45	22.50	

Mount Polley 2010/2011 Drilling

Boundary Zone Underground

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t	Silver ppm
				from	to				
NDU11-173	166	-25.0	178.9	97.2	106.0	8.8	0.49	0.50	4.13
and				137.5	162.5	25.0	0.25	0.15	1.69
NDU11-174	185	-25.0	148.4	97.5	107.4	9.9	1.24	0.97	8.41
and				121.8	127.2	5.5	1.02	0.80	7.61
NDU11-175	196	-24.0	157.6	102.5	116.7	14.2	1.16	1.21	7.52
including				107.5	116.7	9.2	1.61	1.61	10.46
and				135.0	145.0	10.0	1.09	0.74	4.54
NDU11-176	196	-42.0	170.4	120.0	150.0	30.0	0.70	0.41	1.86
including				140.0	150.0	10.0	1.54	0.93	3.72
NDU11-177	274	6.8	69.2	0.0	21.6	21.6	1.43	0.87	8.35
NDU11-178	270	54.0	81.8	0.0	25.0	25.0	3.22	1.62	14.67
including				15.0	22.5	7.5	4.73	2.88	7.50
NDU11-179	302	65.0	101.2	0.0	28.8	28.8	3.12	1.25	16.56
including				17.5	26.0	8.5	5.32	1.65	27.95
and				56.3	85.2	28.9	2.11	1.83	12.49
including				56.3	65.0	8.7	3.71	2.91	23.32
NDU11-180	302	0.0	52.4	0.0	17.5	17.5	1.99	1.38	8.11
including				10.0	17.5	7.5	2.77	2.41	12.90
NDU11-181	331	76.0	89.0	0.0	35.7	35.7	1.97	0.95	11.82
including				27.5	35.7	8.2	2.82	1.55	15.21
and				57.8	65.0	7.2	0.82	0.68	4.29
NDU11-182	283	-71.0	86.3	1.8	28.2	26.4	1.26	0.82	6.01
including				1.8	7.5	5.7	2.92	1.62	13.72
NDU11-183	121	72.0	89.3	0.0	37.5	37.5	1.35	1.04	6.74
including				0.0	7.8	7.8	2.25	0.93	8.60
including				19.0	27.5	8.5	2.96	3.17	15.71
and				67.5	81.2	13.7	1.02	1.20	3.79
NDU11-184	128	37.0	121.3	0.0	26.0	26.0	1.56	0.98	9.01
including				9.3	19.0	9.7	2.94	1.28	15.56
and				37.5	51.8	14.3	0.87	0.72	4.29
NDU11-185	130	-54.0	170.1	0.0	75.8	75.8	2.32	1.24	19.22
including				0.0	12.1	12.1	3.84	1.73	38.99
including				23.4	49.1	25.7	3.04	1.92	24.59
and				109.2	120.0	10.8	1.99	0.75	10.46
NDU11-186	147	-48.0	226.8	0.0	29.0	29.0	2.95	0.99	17.54
including				0.0	5.0	5.0	5.51	1.44	43.30
including				10.7	29.0	18.3	2.99	1.12	14.75
and				52.5	68.3	15.8	0.95	0.42	3.64
and				115.0	141.1	26.1	1.64	1.08	8.32
including				125.0	141.1	16.1	2.20	1.57	12.37
NDU11-187	122	-53.0	114.9	0.0	72.5	72.5	2.02	1.60	15.37
including				0.0	12.1	12.1	3.72	3.69	33.27
NDU11-188	123	-9.0	142.3	0.0	27.5	27.5	4.15	2.05	19.95
including				0.0	12.5	12.5	6.28	2.37	33.22
and				123.1	130.2	7.1	1.97	1.41	18.91
NDU11-189	137	-22.0	151.5	0.0	35.0	35.0	4.80	2.76	39.17
including				0.0	9.1	9.1	7.97	3.45	71.06
including				17.5	30.0	12.5	5.84	4.25	41.86
and				115.0	120.6	5.6	2.44	0.81	17.27
NDU11-190	140	15.0	105.8	0.0	15.0	15.0	4.28	2.79	38.61
and				21.0	30.2	9.3	1.39	0.77	11.56

Mount Polley 2010/2011 Drilling

Boundary Zone Underground

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t	Silver ppm
				from	to				
and				40.8	57.8	17.0	0.69	0.73	2.82
NDU11-191	109	-18.5	158.0	0.0	12.4	12.4	4.15	1.89	34.74
and				125.0	150.0	25.0	0.49	0.45	3.35

| Aug 2011 |

Mount Polley 2010/2011 Drilling

Boundary Zone - cubex drilling

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
BZX-425700	0	-90	42.0	NSI				
BZX-425725	0	-90	42.0	6.0	24.0	18.0	0.71	0.18
BZX-425750	0	-90	42.0	NSI				
BZX-425775	0	-90	42.0	NSI				
BZX-425800	0	-90	42.0	12.0	24.0	12.0	0.29	0.13
BZX-425825	0	-90	42.0	0.0	6.0	6.0	0.40	0.13
BZX-425850	0	-90	42.0	NSI				
BZX-450700	0	-90	42.0	NSI				
BZX-450725	0	-90	42.0	12.0	30.0	18.0	0.24	0.08
BZX-450750	0	-90	42.0	18.0	36.0	18.0	0.46	0.19
BZX-450775	0	-90	42.0	0.0	24.0	24.0	1.05	0.37
BZX-450800	0	-90	42.0	NSI				
BZX-450825	0	-90	42.0	NSI				
BZX-450850	0	-90	42.0	18.0	24.0	6.0	0.51	0.09
BZX-475700	0	-90	42.0	12.0	24.0	12.0	0.27	0.12
BZX-475725	0	-90	42.0	0.0	36.0	36.0	0.48	0.20
BZX-475750	0	-90	42.0	NSI				
BZX-475775	0	-90	42.0	12.0	21.0	9.0	0.47	0.29
BZX-475800	0	-90	42.0	NSI				
BZX-475825	0	-90	42.0	18.0	42.0	24.0	0.19	0.21
BZX-475850	0	-90	42.0	0.0	30.0	30.0	0.20	0.19
BZX-712412	0	-90	42.0	NSI				
BZX-712437	0	-90	42.0	NSI				
BZX-712462	0	-90	42.0	NSI				
BZX-712487	0	-90	42.0	NSI				
BZX-737437	0	-90	42.0	18.0	42.0	24.0	0.64	0.20
BZX-737462	0	-90	42.0	18.0	36.0	18.0	0.26	0.11
BZX-737487	0	-90	42.0	NSI			0.37	0.14
BZX-762437	0	-90	42.0	6.0	18.0	12.0	0.37	0.14
BZX-762462	0	-90	42.0	18.0	36.0	18.0	0.40	0.14
BZX-787437	0	-90	42.0	NSI				
BZX-787462	0	-90	42.0	NSI				
BZX-812437	0	-90	42.0	NSI				
BZX-812462	0	-90	42.0	NSI				
BZX-837437	0	-90	42.0	NSI				
BZX-837462	0	-90	42.0	NSI				
BZX-862437	0	-90	42.0	NSI				
BZX-862462	0	-90	42.0	NSI				
BZX-862487	0	-90	42.0	NSI				
BZX-900485	0	-90	42.0	NSI				
BZX-900510	0	-90	42.0	30.0	42.0	12.0	0.78	0.32
BZX-925500	0	-90	42.0	NSI				
BZX-940485	0	-90	42.0	0.0	18.0	18.0	1.10	0.26
BZX-950510	0	-90	42.0	NSI				
BZX-960500	0	-90	42.0	NSI				

Mount Polley 2010/2011 Drilling

Pond Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
PZ10-52	69	-55	384.3	283.9	296.1	12.2	4.25	1.26
including				290.3	296.1	5.7	8.34	2.22
PZ10-53	77	-58	383.1	252.5	264.3	11.8	0.36	0.19
and				278.0	315.8	37.8	0.36	0.23
PZ10-54	55	-51	334.4	NSI				
PZ10-55	280	-80	326.4	147.5	237.5	90.0	1.23	0.60
including				213.9	229.4	15.5	3.73	2.09
PZ10-56	91	-60	325.2	NSI				
PZ10-57	95	-53	324.0	197.5	269.5	72.0	0.89	0.35
including				218.4	226.3	8.0	2.23	0.44
including				238.8	269.5	30.7	1.26	0.61
PZ10-58	300	-65	325.2	147.5	160.8	13.3	1.93	0.39
PZ10-59	309	-62	268.3	79.6	149.5	69.9	0.40	0.16
including				112.5	124.8	12.3	0.69	0.26
							May 2010	
PZ10-60	240	-50	164.0	21.3	35.0	13.7	0.21	0.24
and				45.0	57.5	12.5	0.14	0.24
							Mar 2011	

Mount Polley 2010/2011 Drilling

Southeast Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
SE10-82	90	-70	249.0	NSI				
SE10-83	90	-60	405.0	NSI				

Mount Polley 2010/2011 Drilling

Northeast Zone

Drill Hole #	Az°	Dip°	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t
				from	to			
WB10-256	60	-60	319.1	185.8	197.1	11.3	0.76	0.42
and				285.0	297.5	12.5	0.50	0.54
WB10-257	60	-70	319.1	NSI				

| May 2010 |