

Drill Hole #	Zone	Easting	Northing	Azimuth (°)	Dip (°)	Total Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver g/t
07-335	East	0452699	6395888	0	-90	1029.0	4.9	1029.0	1024.1	1.01	1.26	3.92
07-336	Main	0452026	6395615	0	-90	1000.7	4.3	1000.7	996.4	0.40	0.38	1.34
07-337	Main	0452026	6395615	0	-75	1050.7	10.7	1050.7	1040.0	0.24	0.23	0.59
and							112.5	445.0	332.5	0.39	0.35	0.78
and							155.0	445.0	290.0	0.39	0.38	0.89
07-338	East	452699	6395888	0	-78	721.5	5.2	721.5	716.3	0.79	0.74	2.02
including							5.2	105.0	99.8	2.15	1.60	7.03
and							675.0	721.5	46.5	1.05	1.67	1.41
07-340*	East	452602	6395904	95	-66	815.9	6.1	760.0	753.9	0.60	0.56	2.07
including							72.5	267.5	195.0	1.11	1.11	3.51
<i>*RC07-340 was drilled from the same collar and orientation as RC07-339, when RC07-339 had to be abandoned</i>												
RC08-341	East	452775	6395881	0	-90	435.0	82.5	435.0	352.5	0.68	0.64	2.65
RC08-342	East	452803	6395890	0	-90	511.8	3.7	511.8	508.1	0.47	0.42	3.03
including							125.0	175.0	270.0	1.03	0.87	8.13
including							472.5	492.5	20.0	0.80	0.89	5.54
RC08-343	East	452572	6395995	0	-90	1273.2	840.3	1273.2	432.9	0.36	0.46	1.13
including							842.5	940.0	97.5	0.63	0.96	1.89
RC09-344	East	452765	6395864	0	-90	331.3	3.7	331.3	327.7	0.37	0.40	1.22
including							125.0	331.3	206.3	0.49	0.50	1.71
including							132.5	211.7	79.2	0.77	0.77	2.64
RC09-345	East	452702	6396000	0	-90	1501.1	426.1	952.5	526.4	0.77	1.37	1.68
including							475.0	518.9	43.9	2.22	3.22	3.35
including							640.0	950.0	310.0	0.80	1.66	2.04
including							833.8	950.0	116.2	1.06	3.11	4.09
and							1035.0	1090.0	55.0	0.40	0.41	1.02
RC09-346	East	452684	6396157	155	-77	1503.9	530.0	1043.6	513.6	0.61	0.91	1.16
including							615.0	806.1	191.1	0.92	1.53	1.20
including							995.0	1043.6	48.6	1.01	1.80	3.61
and							1107.5	1277.5	170.0	0.21	0.16	0.97
RC09-347	East	452675	6395822	0	-90	1315.5	108.0	1240.5	1132.5	0.39	0.46	1.75
including							290.0	410.0	120.0	0.41	0.58	1.01
including							290.0	990.5	700.5	0.47	0.59	2.13
including							697.5	762.5	65.0	1.02	1.34	4.89
including							875.0	990.5	115.5	0.63	0.88	2.50
RC09-348	East	452633	6395912	0	-90	1501.8	42.5	1307.5	1265.0	0.62	0.82	1.95
including							232.0	557.5	325.5	0.85	0.78	2.25
including							302.5	557.5	255.0	0.87	0.84	2.32
including							725.4	969.3	243.9	1.21	2.41	4.64
including							756.0	885.9	129.9	1.52	3.35	5.76
RC09-349	East	452769	6395976	0	-90	1150.6	390.0	1015.3	625.3	0.82	0.93	1.11
including							545.0	582.5	37.5	1.51	1.89	1.54
including							866.6	919.9	53.3	1.83	2.62	2.60
RC09-350	East	452803	6396019	0	-90	1477.4	420.0	1067.5	647.5	1.50	2.68	3.22
including							530.0	962.5	432.5	2.00	3.80	4.42
including							540.0	692.5	152.5	4.12	8.83	10.46
including							692.5	962.5	270.0	0.83	1.02	1.12
including							1030.0	1067.5	37.5	0.65	1.52	0.48

Drill Hole #	Zone	Easting	Northing	Azimuth (°)	Dip (°)	Total Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver g/t
RC09-351	East	452518	6395803	0	-90	1501.1	237.5	732.5	495.0	0.46	0.59	1.21
including							287.5	545.0	257.5	0.54	0.69	1.38
including							425.7	530.0	104.3	0.66	0.96	1.62
and							1092.5	1222.5	130.0	0.30	0.26	0.91
RC09-352	East	452587	6395891	0	-90	1245.0	115.0	852.9	737.9	0.54	0.60	1.61
including							300.0	852.9	552.9	0.62	0.73	1.85
including							407.5	530.0	122.5	0.82	0.67	1.94
including							680.0	850.0	170.0	0.84	1.41	3.33
RC09-353	East	452838	6396063	0	-90	1287.8	67.5	1202.5	1135.0	0.50	0.59	0.71
including							570.0	1020.0	450.0	0.80	1.07	1.03
including							632.5	705.0	72.5	1.16	1.88	1.32
including							912.3	952.5	40.2	0.96	1.14	1.19
RC09-354	East	452684	6395866	38.5	-71	1357.6	6.7	304.1	297.4	1.77	1.69	5.23
including							6.7	120.0	113.3	2.44	1.87	7.38
and							480.0	1297.5	817.5	0.55	0.47	0.82
RC10-355	Saddle	452300	6395700	0	-90	1489.0	335.4	1092.5	757.1	0.38	0.48	1.27
including							1007.5	1065.0	57.5	0.93	1.56	4.19
RC10-360	East	452747	6396021	0	-90	1426.5	473.8	1145.0	671.2	1.03	1.66	1.94
including							560.0	1087.5	527.5	1.19	1.98	2.16
including							607.5	962.5	355.0	1.41	2.59	2.40
including							700.0	755.8	55.8	2.00	4.22	3.25
including							802.5	952.5	150.0	1.83	3.34	3.35
RC10-363	East	453013	6395924	0	-90	1219.6	630.0	655.0	25.0	0.26	0.25	2.68
and							670.0	695.1	25.1	0.36	0.50	0.65
and							728.3	779.6	51.3	0.34	0.69	1.84
and							837.1	849.5	12.4	0.37	0.50	1.26
RC10-366	East	452621	6396293	150	-80	317.5	NSI					
RC10-368	East	452621	6396293	150	-80	1312.8	732.5	1287.5	555.0	0.28	0.26	0.67
including							915.4	1202.5	287.1	0.34	0.35	0.83
including							1010.0	1130.0	120.0	0.41	0.35	1.03
RC10-369	East	453007	6395701	0	-90	1010.4	NSI					
RC10-372	East	452929	6396105	0	-90	1139.0	505.0	682.5	177.5	0.35	0.36	0.71
RC10-375	East	453062	6396057	0	-90	1486.2	297.5	1159.2	861.7	0.41	0.38	0.94
including							530.0	832.5	302.5	0.56	0.54	1.03
including							870.0	923.4	53.4	0.55	0.42	1.18
including							962.5	1152.5	190.0	0.29	0.20	0.72
and							1222.5	1410.0	187.5	0.20	0.13	0.51
RC10-376	East	452796	6396154	0	-90	1065.9	612.4	777.5	165.1	0.26	0.20	0.53
RC10-386	East	452615	6396069	0	-90	1453.0	757.5	1352.5	595.0	0.32	0.35	0.72
including							757.5	1015.0	257.5	0.41	0.48	0.77
RC10-388	Main	451497	6395272	0	-90	1355.5	250.0	1297.3	1047.3	0.22	0.34	0.89
including							352.5	732.5	380.0	0.34	0.50	0.77
including							872.5	910.0	37.5	0.29	0.55	3.83
including							965.0	1050.0	85.0	0.21	0.31	0.83
including							1092.5	1230.0	137.5	0.20	0.33	0.92
RC10-389	East	452832	6395840	0	-90	1156.7	425.0	732.5	307.5	0.47	0.36	1.64
including							492.5	552.5	60.0	0.64	0.50	1.60
and							839.3	1062.5	223.2	0.40	0.32	1.52
and							840.0	927.5	87.5	0.56	0.52	2.29

Drill Hole #	Zone	Easting	Northing	Azimuth (°)	Dip (°)	Total Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver g/t
RC10-390	Main	452197	6395544	0	-90	1167.8	57.5	72.5	15.0	0.33	0.32	0.62
and							117.5	195.0	77.5	0.28	0.24	0.82
and							233.6	259.9	26.3	0.32	0.35	0.38
and							302.5	365.0	62.5	0.19	0.22	2.40
and							452.5	911.6	459.1	0.28	0.20	0.85
and							936.1	977.5	41.4	0.24	0.22	2.79
and							1095.0	1152.5	57.5	0.17	0.15	4.12
RC10-391	East	452880	6395973	0	-90	1325.0	162.5	1165.0	1002.5	0.50	0.38	0.99
including							512.5	680.0	167.5	0.75	0.58	0.97
including							910.0	932.0	22.0	1.04	1.19	2.61
RC10-392	Main	451477	6395487	0	-90	1026.8	247.5	480.0	232.5	0.39	0.48	1.63
including							345.0	432.5	87.5	0.61	0.70	2.73
and							705.0	782.5	77.5	0.11	0.35	0.66
RC10-393	East	452790	6395930	0	-90	1318.3	55.0	1167.5	1112.5	0.54	0.61	1.96
including							617.5	935.0	317.5	1.08	1.46	4.28
including							617.5	652.0	34.5	1.45	1.93	5.39
including							666.5	694.6	28.1	1.18	1.82	4.88
including							722.2	847.5	125.3	1.40	1.87	5.23
including							880.0	937.5	57.5	1.26	1.74	5.84
RC10-394	Saddle	452167	6396081	155	-65	1501.1	472.1	1207.5	735.4	0.32	0.32	1.54
including							567.5	595.8	28.3	1.16	1.12	2.48
RC10-395	Main	451678	6395357	0	-90	1300.6	200.0	245.0	45.0	0.32	0.16	0.54
and							837.5	877.5	40.0	0.21	0.21	1.03
and							1097.2	1172.5	75.3	0.25	0.28	1.68
and							1232.5	1297.5	65.0	0.23	0.18	0.74
RC10-396	Main	451835	6395375	0	-90	983.6	732.5	983.6	251.1	0.33	0.30	1.05
RC10-397	Main	451968	6395326	0	-90	1001.9	27.5	62.5	35.0	0.37	0.18	0.39
and							130.0	537.5	407.5	0.43	0.42	0.93
including							240.0	270.0	30.0	1.13	0.55	1.14
including							387.5	427.5	40.0	0.79	1.09	1.63
and							635.0	675.0	40.0	0.23	0.24	0.59
RC10-398	Saddle	452379	6395628	0	-90	1120.1	112.5	155.0	42.5	0.27	0.31	0.81
and							185.0	425.0	240.0	0.25	0.23	0.98
and							597.2	758.9	161.7	0.30	0.15	3.82
and							600.0	630.0	30.0	0.27	0.19	13.39
and							800.5	1045.0	244.5	0.36	0.36	2.27
RC10-399	Main	451750	6395557	0	-90	1011.2	549.3	570.0	20.7	0.23	0.23	1.04
and							602.5	615.0	12.5	0.37	0.39	1.00
RC10-400	Main	452282	6395363	0	-90	1014.3	90.0	102.5	12.5	0.41	0.17	1.09
and							557.5	582.5	25.0	0.25	0.19	0.80
RC10-401	Saddle	452297	6395809	0	-90	1038.5	347.5	985.0	637.5	0.42	0.39	1.31
including							352.5	437.5	85.0	0.55	0.50	1.13
RC10-402	Main	451847	6395822	0	-90	1089.5	102.5	150.0	47.5	0.26	0.13	0.49
and							277.5	309.5	32.0	0.30	0.16	0.42
and							660.0	751.5	91.5	0.29	0.22	0.74
and							825.0	847.5	22.5	0.23	0.23	0.55

Drill Hole #	Zone	Easting	Northing	Azimuth (°)	Dip (°)	Total Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver g/t
RC10-403	Main	451986	6395997	155	-65	1522.5	337.5	1237.5	900.0	0.25	0.22	0.95
including							337.5	563.7	226.2	0.29	0.28	0.46
including							670.0	775.0	105.0	0.23	0.25	0.80
including							877.5	1237.5	360.0	0.33	0.25	1.63
including							1015.0	1077.5	62.5	0.59	0.35	1.79
including							1125.0	1162.5	37.5	0.52	0.34	3.15
RC10-404	Main	452088	6395658	0	-90	1043.9	55.0	257.5	202.5	0.45	0.44	1.37
including							122.5	177.5	55.0	0.94	0.95	2.27
including							162.5	177.5	15.0	2.43	2.50	2.82
and							324.3	456.8	132.5	0.67	0.76	1.17
including							387.5	415.0	27.5	1.16	1.52	1.71
and							478.4	665.0	186.6	0.20	0.20	0.72
and							687.5	775.0	87.5	0.17	0.21	0.45
and							805.8	830.4	24.6	0.22	0.28	1.41
and							867.5	880.0	12.5	0.31	0.33	0.77
and							925.0	997.5	72.5	0.22	0.23	0.79
RC10-405	East	452644	6395531	0	-90	1001.9	530.0	667.5	137.5	0.29	0.31	0.61
and							827.5	942.5	115.0	0.32	0.48	0.60
RC10-406	Main	451934	6395641	0	-90	986.6	15.0	265.8	250.8	0.43	0.31	0.86
and							15.0	607.5	592.5	0.33	0.26	0.75
including							196.2	212.5	16.3	0.92	1.06	1.11
including							292.3	305.0	12.7	0.30	0.39	0.40
including							345.9	607.5	261.6	0.30	0.27	0.80
and							875.0	915.0	40.0	0.21	0.23	0.49
RC10-407	Main	452016	6395459	0	-90	1053.7	4.0	60.0	56.0	0.39	0.20	0.92
and							4.0	1030.0	1026.0	0.22	0.20	0.97
including							77.5	135.0	57.5	0.70	0.31	1.14
including							214.3	271.0	56.7	0.57	0.22	4.63
including							500.0	540.0	40.0	0.32	0.49	0.59
including							591.3	732.5	141.2	0.29	0.39	1.02
including							770.6	785.0	14.4	0.36	0.35	0.53
including							865.0	1030.0	165.0	0.26	0.29	1.92
RC10-408	Main	452476	6395894	0	-90	1206.1	206.5	235.0	28.5	0.26	0.12	0.38
and							302.5	370.0	67.5	0.24	0.15	0.62
and							502.5	650.0	147.5	0.32	0.33	0.98
and							687.5	754.4	66.9	0.37	0.59	1.33
and							781.2	1060.0	278.8	0.44	0.57	1.34
and							1072.5	1110.0	37.5	0.22	0.17	0.47
RC10-409	Main	452561	6395712	0	-90	1361.5	297.5	1304.5	1007.0	0.30	0.30	1.44
RC10-410	Main	451763	6396003	155	-65	1493.2	535.0	669.3	134.3	0.30	0.23	0.96
and							707.4	820.0	112.6	0.28	0.33	0.44
and							986.2	1000.0	13.8	0.17	0.32	1.12
and							1085.0	1115.0	30.0	0.17	0.58	1.09
RC10-411	East	453250	6396121	0	-90	1075.0	437.5	1047.5	610.0	0.43	0.41	1.27
RC10-412	Main	451320	6395185	0	-90	1029.3	530.0	612.5	82.5	0.27	0.32	0.76
and							530.0	974.3	444.3	0.22	0.27	1.63
including							612.5	643.9	31.4	0.11	0.55	12.64
including							659.0	974.3	315.3	0.23	0.24	0.83
RC10-413	Main	452608	6395847	0	-90	1468.2	45.0	532.2	487.2	0.49	0.40	1.73
including							395.0	500.0	105.0	0.84	0.77	2.76

Drill Hole #	Zone	Easting	Northing	Azimuth (°)	Dip (°)	Total Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver g/t
RC10-414	East	452825	6395623	335	-76	1357.3	557.9	625.0	67.1	0.32	0.26	1.59
and							641.3	1130.4	489.1	0.50	0.66	2.33
including							792.5	813.4	20.9	1.20	1.65	3.57
including							907.5	957.5	50.0	0.62	1.03	2.47
and							1160.0	1185.0	25.0	0.29	0.26	0.89
and							1207.5	1254.7	47.2	0.21	0.24	1.37
and							1296.5	1357.5	61.0	0.30	0.14	0.94
RC10-414	East	452825	6395623	335	-76	1357.3	532.5	567.5	35.0	0.22	0.18	0.77
and							602.5	926.8	324.3	0.52	0.44	1.59
and							1075.0	1160.6	85.6	0.31	0.26	2.98
and							1178.2	1203.6	25.4	0.13	0.09	8.21
RC10-415	East	452647	6395536	120	-45	236.5	NSI					
RC10-416	Main	451663	6395744	0	-90	1001.9	422.5	486.4	63.9	0.31	0.21	1.07
and							530.0	605.0	75.0	0.24	0.23	1.01
and							795.0	862.5	67.5	0.22	0.21	0.49
and							887.5	930.0	42.5	0.23	0.19	0.46
RC10-417	East	452647	6395536	335	-45	166.4	125.0	137.5	12.5	0.26	0.51	0.26
RC10-418	Main	452345	6395226	335	-45	218.2	NSI					
RC10-419	East	452741	6395795	0	-90	1212.2	82.5	167.5	85.0	0.19	0.21	0.32
and							190.4	950.2	759.8	0.45	0.57	1.61
including							392.5	444.9	52.4	0.60	1.61	1.73
including							617.5	637.2	19.7	0.89	0.64	2.10
including							882.5	927.5	45.0	0.73	0.80	2.97
and							1033.9	1051.6	17.7	0.42	0.38	1.15
RC10-420	Main	452071	6395815	0	-90	1001.9	5.2	125.0	119.8	0.38	0.13	0.45
and							300.0	322.5	22.5	0.40	0.28	0.70
and							345.0	355.0	10.0	0.25	0.29	0.47
and							412.5	945.0	532.5	0.22	0.25	0.73
RC10-421	East	452711	6396334	155	-65	1527.3	600.0	1240.0	640.0	0.57	0.67	1.03
including							695.0	815.0	120.0	0.88	1.44	1.49
including							950.0	985.0	35.0	0.72	0.81	1.21
RC10-422	Main	451920	6395193	0	-90	1101.0	207.5	220.0	12.5	0.23	0.19	0.88
and							500.0	515.0	15.0	0.26	0.19	0.92
and							570.0	592.5	22.5	0.23	0.23	0.50
and							817.5	837.5	20.0	0.34	0.27	0.78
RC10-423	East	452569	6395935	0	-90	1257.9	385.0	730.9	345.9	0.68	0.94	2.16
including							500.0	515.0	15.0	1.05	0.82	3.52
including							537.5	557.5	20.0	0.70	1.15	2.32
including							627.5	730.9	103.4	0.97	1.88	3.47
including							697.5	712.5	15.0	2.07	5.11	7.03
and							820.4	1037.3	216.9	1.15	2.44	5.79
including							820.4	879.8	59.4	2.93	6.85	15.44
including							860.0	875.0	15.0	3.65	12.59	18.67
and							1050.6	1165.0	114.4	0.39	0.44	1.30
RC10-424	East	452573	6396159	0	-90	1001.9	NSI					
RC10-425	East	452653	6395757	0	-90	1550.5	122.5	239.0	116.5	0.36	0.42	0.82
and							302.5	1065.0	762.5	0.33	0.37	1.40
and							1197.5	1260.0	62.5	0.42	0.20	1.09
and							1457.5	1470.0	12.5	0.36	0.14	1.02

Drill Hole #	Zone	Easting	Northing	Azimuth (°)	Dip (°)	Total Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver g/t
RC10-426	East	452281	6396325	155	-63	1513.3	814.9	975.0	160.1	0.74	0.76	1.49
including							835.0	847.5	12.5	1.46	1.82	1.67
including							865.0	890.0	25.0	1.08	1.03	2.20
and							982.5	995.0	12.5	0.21	0.17	0.47
and							1010.0	1042.5	32.5	0.24	0.20	0.61
and							1077.8	1117.5	39.7	0.23	0.18	0.98
and							1135.0	1147.5	12.5	0.28	0.25	0.83
RC10-427	Main	452463	6395446	335	-70	1498.7	190.0	205.0	15.0	0.23	0.50	0.98
and							302.5	382.5	80.0	0.20	0.23	0.95
and							605.0	1044.1	439.1	0.29	0.27	1.20
and							1060.0	1079.6	19.6	0.17	0.39	4.37
and							1197.5	1209.1	11.6	0.13	2.11	25.99
RC10-428	Main	452255	6395184	0	-90	1016.5	NSI					
RC11-429	Saddle	452212	6395988	0	-90	1251.8	750.0	1152.5	402.5	0.37	0.42	0.70
including							797.5	867.5	70.0	0.71	0.91	1.08
and							1202.5	1251.8	49.3	0.23	0.21	0.69
RC11-430	East	452492	6396335	155	-65	1470.7	667.5	855.0	187.5	0.26	0.26	0.48
and							1064.6	1227.5	162.9	0.34	0.54	1.54
including							1067.5	1097.5	30.0	0.61	1.30	2.61
and							1247.5	1257.5	10.0	0.42	0.50	1.20
and							1282.5	1360.0	77.5	0.26	0.33	1.08
RC11-431	East	452966	6396013	0	-90	1312.8	172.5	1250.0	1077.5	0.44	0.29	0.84
RC11-432	Main	452297	6395703	65	-65	1189.8	175.0	1144.9	969.9	0.40	0.54	2.07
including							595.0	615.0	20.0	1.01	1.85	5.57
including							1117.5	1142.5	25.0	0.80	1.36	15.15
RC11-441	East	452923	6395882	0	-90	1183.2	480.0	662.5	182.5	0.30	0.37	1.05
and							682.5	1005.0	322.5	0.30	0.21	1.72
RC11-444	East	452682	6396033	0	-90	151.5	NSI					
RC11-445	Saddle	452294	6395810	335	-76	1482.9	177.5	237.5	60.0	0.25	0.21	0.39
and							252.5	287.5	35.0	0.28	0.23	0.57
and							337.5	1100.0	762.5	0.43	0.48	0.84
and							1175.0	1282.5	107.5	0.24	0.21	0.72
RC11-446	East	453016	6395935	0	-90	151.5	NSI					
RC11-450	East	452391	6396075	0	-90	1243.9	NSI					
RC11-477	Gully	450701	6394750	0	-90	1482.9	172.5	980.0	807.5	0.31	0.29	1.61
including							230.0	657.5	427.5	0.39	0.35	1.93
including							333.6	435.0	101.4	0.58	0.45	3.34
and							1405.0	1437.5	32.5	0.28	0.30	1.01
RC11-539	Gully	450605	6394931	155	-75	1263.4	275.4	862.5	587.1	0.41	0.41	2.05
including							347.5	362.5	15.0	0.66	1.01	6.90
and							917.3	952.5	35.2	0.27	0.25	1.07
RC11-564	Gully	450870	6394816	0	-90	1077.5	18.3	567.0	548.7	0.35	0.36	2.54
including							18.3	282.3	264.0	0.48	0.52	3.19
and							743.8	757.1	13.3	0.25	1.07	1.10
and							922.5	934.7	12.2	0.47	0.73	1.27
and							962.5	1020.0	57.5	0.23	0.33	1.12
RC11-565	East Ridge	453570	6395932	335	-60	1071.4	500.0	560.0	60.0	0.23	0.09	0.77
							645.0	795.0	150.0	0.31	0.14	0.69
RC11-566	East Ridge	454369	6396339	335	-65	1296.9	NSI					

Drill Hole #	Zone	Easting	Northing	Azimuth (°)	Dip (°)	Total Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver g/t
RC12-580	Gully	450605	6394932	0	-90	1182.7	335.0	940.8	605.8	0.39	0.43	2.00
including							495.0	542.5	47.5	1.00	1.06	3.87
including							627.5	722.5	95.0	0.77	0.73	2.69
and							1045.0	1077.5	32.5	0.01	0.68	1.63
RC12-581	Gully	450305	6395100	155	-65	991.2	853.8	952.5	98.7	0.14	0.17	0.72
RC12-582	Saddle	452191	6396278	155	-70	1037.8	845.0	1037.8	192.8	0.34	0.30	0.98
RC12-583	Saddle	452120	6395931	0	-90	1196.0	549.5	1057.5	508.0	0.24	0.22	0.58
including							1000.0	1057.5	57.5	0.42	0.31	0.87
RC12-584	East	453109	6396185	0	-90	1007.4	480.0	687.5	207.5	0.18	0.09	0.36
and							747.5	875.0	127.5	0.20	0.10	0.45