

# Mount Polley 2003-2005 Drilling

## Northeast Zone (1)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval		Interval Length	Copper %	Gold g/t	Silver ppm
				from	to				
WB03 01	240	-90	184.7	3.1	- 60.0	57.0	2.54	1.15	17.40
WB03 02	240	-60	215.2	2.6	- 79.1	76.5	0.74	0.34	5.00
WB03 03	240	-60	224.3	1.5	- 195.0	193.5	1.33	0.44	10.60
WB03 04	240	-60	224.3	0.6	- 159.0	158.4	0.34	0.21	2.66
WB03 05	240	-60	242.6	3.7	- 37.5	33.8	0.49	0.30	5.32
WB03 06	240	-60	245.7	7.1	- 220.0	212.9	0.98	0.32	6.18
<i>including</i>				7.1	- 110.0	102.9	1.94	0.57	11.71
WB03 07	240	-60	230.4	13.4	- 217.5	204.1	1.02	0.40	7.31
<i>including</i>				13.4	- 126.3	112.9	1.72	0.56	12.33
WB03 08	240		232.9	7.3	- 81.1	73.8	0.98	0.31	8.04
WB03 09	60		172.2	0.0	- 132.5	132.5	1.04	0.24	6.53
<i>including</i>				62.5	- 132.5	70.0	1.69	0.39	10.38
WB03 10	240		212.1	21.3	- 163.6	142.3	1.16	0.40	8.20
WB03 11	240		221.3	24.4	- 205.0	180.6	1.00	0.40	7.30
WB03 12	60		123.1	0.0	- 15.2	15.2	0.72	0.23	6.65
WB03 13	260		53.6	abandoned					
WB03 14	240		230.1	44.3	- 213.3	169.0	1.06	0.37	6.65
<i>including</i>				55.0	- 90.0	35.0	2.02	0.79	12.81
WB03 15	240		221.3	30.0	- 165.0	135.0	1.16	0.35	9.58
<i>including</i>				47.5	- 120.0	72.5	1.82	0.55	16.17
WB03 16	240		184.7	15.2	- 127.5	112.3	0.63	0.20	4.02
<i>including</i>				15.2	- 37.5	22.3	1.41	0.48	9.61
WB03 17	40		159.1	39.6	- 74.2	34.6	1.18	0.09	10.91
WB03 18	60	-50	130.2	85.0	- 97.5	12.5	0.14	0.06	0.06
WB03 19	60	-50	325.2	145.3	- 265.0	119.7	1.02	0.20	9.61
<i>including</i>				147.5	- 195.0	47.5	1.73	0.45	20.32
WB03 20	60	-80	181.1	159.1	- 172.5	13.4	0.17	0.06	0.74
WB03 21	60	-80	306.9	26.5	- 235.0	208.5	1.18	0.45	9.05
<i>including</i>				26.5	- 137.5	111.0	1.78	0.79	15.34
WB04-22	240	-60	215.5	95.0	- 162.5	67.5	2.00	0.94	12.83
WB04-23	60	-50	277.4	62.5	- 195.0	132.5	1.22	0.53	8.48
<i>including</i>				123.5	- 185.0	61.5	2.18	0.90	14.37
WB04-24	60	-50	221.6	47.5	- 195.3	147.8	1.46	0.31	8.92
<i>including</i>				112.5	- 187.5	75.0	2.50	0.52	15.04
WB04-25	60	-50	136.3	9.1	- 67.5	58.4	1.86	0.72	15.09
<i>including</i>				25.0	- 40.0	15.0	4.38	1.92	38.99
WB04-26	60	-50	230.7	130.0	- 217.5	87.5	0.72	0.22	3.92
<i>including</i>				137.5	- 190.0	52.5	1.01	0.34	5.90
WB04-27	60	-50	355.7	200.0	- 241.0	41.0	0.87	0.30	6.68
<i>and</i>				266.6	- 307.5	40.9	1.36	0.14	3.41
WB04-28	60	-50	385.6	239.6	- 353.3	113.7	0.62	0.25	3.20
<i>including</i>				255.0	- 297.5	42.5	0.92	0.46	4.13
WB04-29	240	-85	285.0	21.3	- 158.2	136.9	1.14	0.44	8.57
<i>and</i>				211.8	- 235.0	23.2	0.54	0.35	3.10
WB04-30	60	-50	197.2	25.0	- 147.5	122.5	1.64	0.32	11.63
<i>including</i>				52.5	- 78.3	25.8	3.51	0.96	26.84

: assay data released September 2003 through February 2004

# Mount Polley 2003-2005 Drilling

## Northeast Zone (2)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver ppm
WB04-31	60	-50	136.3	40.0	- 115.6	75.6	0.50	0.20	5.05
<i>including</i>				40.0	- 64.3	24.3	0.66	0.29	7.99
<i>and</i>				102.5	- 115.6	13.1	1.00	0.49	7.10
WB04-32	240	-60	386.2	65.0	- 77.5	12.5	0.45	0.01	3.00
<i>and</i>				149.8	- 237.5	87.7	0.65	0.16	2.95
<i>including</i>				150.0	- 187.5	37.5	1.02	0.14	3.31
WB04-33	240	-60	214.9	42.5	- 45.3	2.8	1.28	0.60	10.02
WB04-34	60	-80	270.1	172.5	- 180.0	7.5	0.91	0.07	2.30
<i>and</i>				205.5	- 217.5	12.0	0.51	0.05	2.02
WB04-35	240	-60	224.3	no significant intercepts					
WB04-36	60	-50	221.6	22.5	- 55.0	32.5	0.55	0.20	5.42
<i>and</i>				115.0	- 132.5	17.5	1.04	0.63	6.47
WB04-37	60	-50	248.1	177.5	- 202.5	25.0	0.62	0.11	4.42
WB04-38	240	-50	248.7	8.2	- 50.0	41.8	2.16	0.66	12.51
<i>and</i>				80.2	- 87.5	7.3	0.46	0.17	4.97
WB04-39	60	-50	120.4	12.5	- 55.0	42.5	1.17	0.43	8.04
WB04-40	60	-50	153.9	7.5	- 15.0	7.5	0.47	0.16	4.27
<i>and</i>				75.0	- 95.0	20.0	0.85	0.59	7.18
WB04-41	240	-50	193.9	75.3	- 79.0	3.7	1.15	0.11	4.71
<i>and</i>				92.3	- 94.3	2.0	2.21	0.22	6.80
<i>and</i>				120.8	- 135.3	14.5	1.27	0.93	7.80
WB04-42	60	-50	248.4	160.0	- 165.0	5.0	0.50	0.13	4.25
WB04-43	60	-50	157.3	48.4	- 97.6	49.2	2.09	0.93	12.05
<i>including</i>				48.4	- 67.0	18.6	4.23	2.15	23.53
WB04-44	60	-50	175.6	3.1	- 47.5	44.4	0.45	0.08	3.36
<i>and</i>				80.0	- 135.0	55.0	1.52	0.24	10.20
WB04-45	60	-50	279.5	93.6	- 115.0	21.4	0.42	0.15	2.80
<i>and</i>				137.5	- 215.0	77.5	1.02	0.38	5.67
WB04-46	60	-50	216.4	25.0	- 45.0	20.0	0.82	0.99	7.80
<i>and</i>				77.5	- 86.0	8.5	0.88	0.49	9.03
<i>and</i>				102.5	- 112.5	10.0	0.43	0.11	3.88
WB04-47	60	-50	319.1	205.0	- 245.0	40.0	0.98	0.44	5.03
<i>and</i>				282.5	- 291.7	9.2	0.46	0.15	2.58
WB04-48	240	-50	227.4	172.5	- 212.5	40.0	0.67	0.36	4.71
<i>including</i>				187.5	- 199.8	12.3	1.16	0.61	7.79
WB04-49	240	-60	215.5	135.4	- 140.0	4.6	0.56	0.18	3.80
<i>and</i>				158.6	- 170.0	11.4	0.75	0.54	4.98
WB04-50	240	-60	246.0	85.0	- 167.5	82.5	1.30	0.20	9.15
WB04-51	60	-50	419.7	no significant intercepts					

: assay data released April 2004

# Mount Polley 2003-2005 Drilling

## Northeast Zone (3)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver ppm	
WB04-52	240	-60	242.6	56.7	-	122.5	65.8	0.60	0.19	3.96
<i>including</i>				56.7	-	68.4	11.7	1.83	0.46	11.45
WB04-53	60	-50	171.6	10.0	-	144.3	134.3	1.70	0.56	10.62
<i>including</i>				17.5	-	81.4	63.9	1.87	0.49	11.85
<i>including</i>				96.5	-	128.5	32.0	2.99	0.44	17.58
WB04-54	60	-50	230.1	88.0	-	102.5	14.5	0.36	0.02	2.55
<i>and</i>				137.5	-	195.0	57.5	1.09	0.34	7.25
WB04-55	60	-50	185.0	3.1	-	10.0	7.0	0.79	0.61	7.84
<i>and</i>				68.4	-	76.7	8.3	0.31	0.13	3.54
<i>and</i>				95.5	-	122.5	27.0	0.55	0.20	4.27
WB04-56	60	-50	215.5	85.0	-	195.4	110.4	1.11	0.33	8.17
WB04-57		-90	170.1	105.0	-	107.5	2.5	1.30	0.06	12.20
WB04-58		-90	209.1	142.5	-	144.4	1.9	0.72	0.20	3.54
WB04-59	60	-50	224.6	27.5	-	176.8	149.3	1.37	0.58	11.15
<i>including</i>				27.5	-	107.5	80.0	2.32	1.07	19.70
<i>including</i>				57.5	-	75.0	17.5	4.93	3.81	42.00
WB04-60	60	-50	273.4	137.3	-	242.5	105.2	1.03	0.34	8.49
<i>including</i>				155.0	-	176.6	21.6	2.70	1.19	27.10
WB04-61	240	-60	155.8	26.9	-	112.5	85.6	0.56	0.25	3.73
WB04-62		-90	126.8	no significant intercepts						
WB04-63	60	-50	352.7	139.5	-	289.5	150.0	0.48	0.09	1.92
WB04-64	60	-50	269.8	90.0	-	237.5	147.5	0.59	0.18	3.52
<i>including</i>				182.9	-	200.0	17.2	2.82	3.52	14.12
WB04-65	60	-50	306.3	172.5	-	280.0	107.5	0.76	0.36	4.27
WB04-66	60	-50	300.8	205.0	-	257.7	52.7	0.61	0.61	4.99
WB04-67		-90	215.8	no significant intercepts						
WB04-68		-90	309.7	132.5	-	135.2	2.7	0.36	0.27	1.60
WB04-69	240	-60	249.0	no significant intercepts						
WB04-70	60	-50	200.3	17.5	-	25.0	7.5	0.35	0.35	2.00
WB04-71		-90	235.6	70.0	-	72.5	2.5	0.64	0.41	2.40
<i>and</i>				85.0	-	88.3	3.3	0.33	0.17	1.93
<i>and</i>				107.5	-	108.2	0.7	1.66	2.70	4.30
<i>and</i>				187.5	-	192.5	5.0	0.40	0.16	2.15

: assay data released May 2004

# Mount Polley 2003-2005 Drilling

## Northeast Zone (4)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver ppm	
WB04-72		-90	216.4	30.0	-	32.3	2.3	0.57	0.26	2.90
<i>and</i>				72.5	-	75.0	2.5	0.75	1.85	5.50
<i>and</i>				123.8	-	130.0	6.2	0.36	0.44	1.30
WB04-73	240	-45	306.3	13.4	-	15.0	1.6	0.50	0.27	3.20
<i>and</i>				267.5	-	270.0	2.5	0.81	0.62	8.40
WB04-74			318.8	220.0	-	225.4	5.4	0.28	0.29	0.92
<i>and</i>				285.0	-	287.5	2.5	1.47	0.86	8.30
WB04-75		-60	209.1	75.0	-	77.5	2.5	1.34	0.26	12.80
WB04-76		-60	203.3	no significant intercepts						
WB04-77		-60	242.9	62.5	-	65.0	2.5	0.01	0.73	0.60
WB04-78		-60	198.1	no significant intercepts						
WB04-79		-90	254.8	15.2	-	46.6	31.4	0.23	0.05	1.15
<i>and</i>				230.0	-	232.5	2.5	0.28	0.43	1.20
WB04-80	60	-70	270.4	25.0	-	30.0	5.0	0.56	0.47	3.55
<i>and</i>				60.0	-	62.5	2.5	0.77	1.00	3.90
WB04-81	60	-50	319.1	97.5	-	145.4	47.9	0.63	0.08	7.49
<i>including</i>				105.0	-	115.0	10.0	1.82	0.27	27.85
WB04-82	240	-45	182.4	170.8	-	175.6	4.8	1.05	0.78	4.17
<i>and</i>				127.5	-	145.0	17.5	0.20	0.12	1.04
<i>and</i>				127.5	-	136.5	9.0	0.20	0.12	1.03
<i>and</i>				132.5	-	132.8	0.3	0.76	0.31	2.70
<i>including</i>				90.0	-	92.5	2.5	0.69	0.10	2.60
<i>including</i>				80.9	-	82.5	1.6	1.05	0.22	3.00
WB04-83	60	-45	334.4	85.0	-	93.8	8.8	0.49	0.27	2.05
<i>and</i>				112.5	-	170.0	57.5	0.42	0.18	1.57
<i>including</i>				142.5	-	157.5	15.0	0.81	0.22	2.93
WB04-84	60	-45	249.0	72.5	-	85.0	12.5	0.37	0.04	1.66
WB04-85	240	-45	242.9	no significant intercepts						
WB04-86	60	-55	224.6	140.0	-	149.0	9.0	0.27	0.42	1.35
WB04-87	240	-60	200.3	103.1	-	132.7	29.7	1.46	0.18	13.71
WB04-88	60	-50	340.5	193.0	-	205.1	12.2	0.619	0.718	3.903
<i>and</i>				229.6	-	282.5	52.9	0.49	0.06	1.65
WB04-89	60	-50	236.8	72.5	-	75.0	2.5	1.52	0.86	3.10
WB04-90	240	-60	267.3	171.2	-	195.6	24.4	0.59	0.04	4.00
<i>and</i>				212.5	-	220.0	7.5	0.52	0.14	4.23
WB04-91	240	-60	282.6	181.5	-	195.0	13.5	.41	.05	3.26
WB04-92	240	-60	349.6	202.5	-	267.2	64.7	0.85	0.25	5.24
<i>including</i>				202.2	-	267.2	47.0	1.27	0.24	6.41
<i>and</i>				293.0	-	320.0	27.0	0.32	0.14	1.79
WB04-93	240	-60	215.5	27.4	-	162.5	135.1	1.40	0.30	14.26
<i>including</i>				60.0	-	112.5	52.5	2.88	0.64	30.78
WB04-94	60	-63	367.9	152.5	-	165.0	12.5	0.63	0.10	7.12
<i>including</i>				222.7	-	243.1	20.4	0.41	0.40	3.61
WB04-95	0	-90	322.2	27.3	-	197.3	170.1	1.48	0.43	11.51
<i>including</i>				27.4	-	122.5	95.1	2.17	0.66	18.67

: assay data released August 2004

# Mount Polley 2003-2005 Drilling

## Northeast Zone (5)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from to	Interval Length	Copper %	Gold g/t	Silver ppm
WB04-96	60	-50	229.3	36.6 - 74.4	37.8	0.36	0.14	1.68
WB04-97	60	-50	285.3	50.0 - 57.5	7.5	0.45	0.13	2.93
<i>and</i>				97.5 - 102.5	5.0	0.36	0.13	1.90
WB04-98	240	-60	383.1	302.5 - 365.0	62.5	1.48	0.50	9.05
WB04-99	240	-80	492.0	190.0 - 440.0	250.0	0.83	0.25	6.20
<i>including</i>				400.0 - 440.0	40.0	1.18	0.70	11.62
WB04-100	240	-60	346.6	no significant intercepts				
WB04-101	240	-80	431.9	280.0 - 377.5	97.5	0.74	0.27	2.93
WB04-102	60	-70	489.5	215.3 - 442.5	227.3	1.11	0.41	7.52
WB04-103	240	-80	447.1	no significant intercepts				
WB04-104	60	-70	587.0	81.2 - 118.2	37.0	1.43	0.69	11.29
<i>and</i>				187.5 - 304.0	116.5	0.90	0.06	6.27
<i>and</i>				346.7 - 420.0	73.3	1.10	0.58	8.23
WB04-105	240	-80	413.0	no significant intercepts				
WB04-106	250	-80	413.0	23.1 - 57.5	34.4	1.44	0.48	16.24
<i>and</i>				195.0 - 250.4	55.4	0.90	0.12	6.71
<i>and</i>				325.0 - 399.0	74.0	0.56	0.36	3.62
WB04-107	60	-70	349.3	95.0 - 117.5	22.5	1.32	0.17	9.49
WB04-108	60	-70	443.7	255.0 - 259.2	4.2	0.72	0.46	7.64
<i>and</i>				300.0 - 317.5	17.5	0.36	0.29	3.11
WB04-109	60	-70	529.0	287.5 - 410.0	122.5	0.85	0.17	5.77
WB04-110	60	-70	352.3	92.5 - 167.5	75.0	2.02	0.62	13.87
<i>and</i>				201.7 - 213.2	11.5	0.47	0.12	3.81
WB04-111	60	-70	443.7	127.5 - 137.5	10.0	0.47	0.31	3.70
<i>and</i>				202.5 - 232.5	30.0	0.89	0.02	4.21
<i>and</i>				274.9 - 284.0	9.1	1.90	0.04	16.85
<i>and</i>				350.0 - 357.5	7.5	0.94	0.11	5.14
WB04-112	60	-70	377.0	63.3 - 97.6	34.3	1.72	0.62	15.12
<i>and</i>				245.0 - 267.2	22.2	0.71	0.02	4.94
WB04-113	60	-70	404.1	97.5 - 155.0	57.5	1.72	0.16	9.99
<i>and</i>				187.5 - 241.6	54.1	0.67	0.15	3.92
<i>and</i>				290.2 - 300.0	9.8	0.30	0.44	2.00

: assay data released August 2004 through November 2004

# Mount Polley 2003-2005 Drilling

## Northeast Zone (6)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from to	Interval Length	Copper %	Gold g/t	Silver ppm
WB04-114	60	-50	169.7	no significant intercepts				
WB04-115	240	-80	471.5	207.5 - 235.0	27.5	0.68	0.02	4.12
<i>and</i>				292.5 - 417.5	125.0	0.79	0.26	4.94
WB04-116	60	-60	218.5	no significant intercepts				
WB04-117	240	-80	438.0	322.5 - 377.5	55.0	0.65	0.27	4.75
WB04-118	60	-70	313.0	112.5 - 135.9	23.4	0.69	0.10	4.32
<i>and</i>				144.4 - 151.8	7.4	0.78	0.29	6.03
WB04-119	70	-60	175.8	no significant intercepts				
WB04-120	60	-70	404.1	207.6 - 222.5	14.9	1.15	0.17	10.24
WB04-121	65	-60	139.2	no significant intercepts				
WB04-122	60	-70	501.0	195.0 - 232.5	37.5	0.71	0.83	8.27
<i>and</i>				273.6 - 366.5	92.9	1.28	0.07	8.24
<i>and</i>				395.0 - 410.0	15.0	0.61	0.10	4.35
WB04-123	60	-70	273.4	150.0 - 222.5	72.5	1.11	0.19	9.61
WB04-124	60	-60	121.0	no significant intercepts				
WB04-125	60	-70	313.0	121.5 - 155.3	33.8	0.69	0.25	4.65
WB04-126	60	-60	160.6	no significant intercepts				
WB04-127	60	-70	660.5	437.5 - 447.5	10.0	0.75	1.16	6.30
<i>and</i>				496.5 - 509.3	12.8	1.52	0.47	11.60
<i>and</i>				519.6 - 584.1	64.5	0.94	0.31	7.15
<i>including</i>				519.6 - 541.9	22.3	1.81	0.44	13.85
WB04-128	60	-70	255.1	102.5 - 117.5	15.0	0.23	0.54	3.20
WB04-129	60	-60	148.4	no significant intercepts				
WB04-130	60	-60	159.0	no significant intercepts				
WB04-131	240	-60	472.5	100.0 - 105.0	5.0	0.45	0.30	3.90
<i>and</i>				232.5 - 240.0	7.5	0.49	0.24	3.98
WB04-132	60	-60	157.6	no significant intercepts				
WB04-133	240	-70	575.2	121.2 - 157.5	36.3	0.71	0.14	4.90
<i>and</i>				173.6 - 180.1	6.5	0.69	0.03	4.99
<i>and</i>				220.0 - 465.0	245.0	0.87	0.33	5.31
<i>including</i>				220.0 - 367.5	147.5	1.21	0.34	7.23
<i>including</i>				283.7 - 302.5	18.8	1.71	0.93	11.36
WB04-134	240	-80	505.1	300.0 - 305.7	5.7	0.70	0.35	4.59
<i>and</i>				387.5 - 465.0	77.5	0.82	0.31	6.30
<i>including</i>				387.5 - 421.3	33.8	1.11	0.41	8.58
<i>and</i>				435.0 - 465.0	30.0	0.83	0.33	6.43
WB04-135	60	-60	202.3	no significant intercepts				
WB04-136	60	-60	150.9	36.8 - 40.9	4.1	0.39	0.13	1.01
WB04-137	240	-80	543.8	no significant intercepts				
WB04-138	60	-70	559.9	107.8 - 112.5	4.7	0.69	0.35	5.58
<i>and</i>				155.0 - 170.0	15.0	0.82	0.43	6.05
<i>and</i>				219.8 - 354.9	135.1	1.03	0.16	6.36
<i>including</i>				223.7 - 242.5	18.8	1.98	0.23	11.23
<i>and</i>				380.6 - 394.2	13.6	0.67	0.12	4.34

: assay data released November 2004 through December 2004

# Mount Polley 2003-2005 Drilling

## Northeast Zone (7)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from to	Interval Length	Copper %	Gold g/t	Silver ppm
WB04-139	60	-60	188.1	no significant intercepts				
WB04-140	60	-60	169.8	no significant intercepts				
WB04-141	60	-70	550.8	237.5 - 250.0	12.5	0.49	0.36	5.10
WB04-142	240	-80	598.3	216.8 - 237.5	20.7	0.58	0.28	4.28
<i>and</i>				280.0 - 300.0	20.0	0.53	0.21	2.76
<i>and</i>				335.3 - 340.0	4.7	0.96	0.91	6.18
<i>and</i>				485.0 - 522.5	37.5	0.60	0.26	4.43
WB04-143	60	-60	151.5	no significant intercepts				
WB04-144	60	-60	157.6	no significant intercepts				
WB04-145	60	-60	163.7	no significant intercepts				
WB04-146	60	-70	474.6	no significant intercepts				
WB04-147	60	-60	151.5	no significant intercepts				
WB04-148	60	-60	118.0	no significant intercepts				
WB04-149	240	-80	556.9	190.0 - 262.1	72.1	0.94	0.17	5.44
<i>and</i>				295.2 - 355.0	59.8	0.69	0.20	4.23
WB04-150	240	-60	629.4	220.0 - 227.4	7.4	0.49	0.34	5.85
<i>and</i>				480.0 - 490.0	10.0	0.67	0.09	3.25
WB04-151	60	-60	163.7	no significant intercepts				
WB04-152	240	-60	599.2	512.0 - 516.1	4.1	0.87	0.03	4.39
WB04-153	240	-80	629.7	146.0 - 151.6	5.6	1.36	0.21	12.04
<i>and</i>				318.0 - 323.6	5.6	0.57	0.32	3.64
<i>and</i>				534.8 - 540.0	5.2	0.38	0.28	1.98
WB04-154	60	-70		no significant intercepts				
WB04-155	60	-70	605.6	290.0 - 398.9	108.9	0.77	0.16	5.13
<i>and</i>				470.0 - 485.0	15.0	0.51	0.44	3.62
WB04-156	60	-70	563.0	355.0 - 360.9	5.9	0.57	0.32	5.52
WB04-157	60	-70	579.1	261.8 - 268.7	6.9	0.78	0.31	4.43
<i>and</i>				510.0 - 515.0	5.0	0.65	0.45	5.40
WB04-158	60	-70	505.1	212.5 - 339.0	126.5	0.55	0.20	3.06
<i>and</i>				350.0 - 355.0	5.0	2.78	1.50	18.83
<i>and</i>				381.1 - 389.0	7.9	3.57	2.41	22.97
<i>and</i>				397.1 - 407.7	10.6	5.43	3.08	30.22
WB04-159	60	-70	237.2	38.8 - 57.5	18.7	2.12	0.59	10.12
WB04-160	60	-70	566.0	137.5 - 144.2	6.7	2.04	0.44	9.47
<i>and</i>				170.1 - 175.0	4.9	0.64	0.02	5.95
<i>and</i>				340.0 - 395.0	55.0	0.80	1.07	5.41
<i>and</i>				417.5 - 425.0	7.5	0.50	0.31	3.57
<i>and</i>				437.5 - 490.9	53.4	0.82	0.43	5.13
<i>and</i>				532.8 - 539.0	6.2	1.91	0.29	14.93
WB04-161	60	-70	495.9	57.8 - 100.0	42.2	1.51	0.35	9.75
<i>and</i>				237.5 - 312.5	75.0	1.69	0.06	11.20
<i>and</i>				332.5 - 358.4	25.9	0.70	0.15	4.65
<i>and</i>				372.5 - 397.6	25.1	4.43	1.28	26.92
<i>including</i>				377.5 - 395.0	17.5	5.41	1.52	33.00
WB04-162	60	-70	297.8	no significant intercepts				

: assay data released December 2004 through January 2005

# Mount Polley 2003-2005 Drilling

## Northeast Zone (8)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from to	Interval Length	Copper %	Gold g/t	Silver ppm	
WB04-163	60	-70	253.6	95.0 - 125.0	30.0	0.35	0.18	3.28	
<i>and</i>				202.5 - 222.2	19.7	0.45	0.29	3.44	
WB04-164	60	-70	236.8	103.8 - 140.0	36.2	0.57	0.04	4.30	
WB04-165	60	-70	178.9	115.0 - 120.3	5.3	0.36	0.48	3.34	
WB04-166	60	-70	252.1	112.5 - 226.4	113.9	0.65	0.14	4.18	
<i>including</i>				125.0 - 160.0	35.0	1.18	0.08	7.55	
WB04-167	60	-70	230.7	124.5 - 130.0	5.5	0.43	0.42	3.54	
WB04-168	60	-70	596.5	337.5 - 352.5	15.0	0.82	0.75	6.40	
<i>and</i>				382.0 - 387.5	5.5	0.64	0.22	4.98	
WB04-169	60	-70	270.4	95.0 - 206.3	111.3	0.72	0.15	5.24	
<i>including</i>				102.5 - 126.9	24.4	1.11	0.12	7.73	
<i>including</i>				187.5 - 206.3	18.8	1.04	0.38	8.52	
<i>and</i>				227.5 - 240.0	12.5	0.52	0.11	3.76	
WB04-170	60	-70	271.3	119.5 - 160.8	41.3	0.94	0.22	4.84	
<i>including</i>				120.0 - 145.0	25.0	1.24	0.33	6.14	
<i>and</i>				218.1 - 244.6	26.5	0.87	0.15	6.00	
WB04-171	60	-50	206.4	no significant intercepts					
WB04-172	60	-70	555.4	100.0 - 143.0	43.0	0.77	0.17	4.95	
<i>and</i>				197.8 - 219.4	21.6	1.15	0.03	11.09	
<i>and</i>				275.6 - 467.5	191.9	0.98	0.29	5.93	
<i>including</i>				275.6 - 365.0	89.4	1.59	0.36	9.56	
WB04-173	60	-50	248.7	no significant intercepts					
WB04-174	60	-50	160.0	no significant intercepts					
WB04-175	60	-50	166.1	no significant intercepts					
WB04-176	60	-50	397.8	237.5 - 275.0	37.5	0.67	0.13	3.44	
<i>and</i>				312.5 - 360.0	47.5	1.00	0.08	2.73	
WB04-177	60	-70	127.1	no significant intercepts					
WB04-178	60	-70	333.8	253.1 - 277.5	24.4	0.67	0.50	5.31	
WB04-179	60	-70	501.7	337.5 - 382.4	44.9	2.19	1.19	14.45	
<i>including</i>				367.5 - 382.4	15.0	5.86	3.13	39.06	
<i>and</i>				404.9 - 407.8	2.9	6.64	4.44	33.02	
WB04-180	60	-70	170.0	no significant intercepts					
WB04-181	60	-70	163.7	112.5 - 149.2	36.7	1.19	0.53	10.17	
<i>including</i>				125.4 - 149.2	23.8	1.56	0.67	13.55	
WB04-182	60	-50	258.2	205.0 - 226.9	21.9	0.23	0.41	2.94	
WB04-183	60	-50	362.5	219.4 - 320.0	100.6	0.62	0.34	3.56	
<i>including</i>				230.0 - 240.9	10.9	1.31	1.10	10.15	
WB04-184	60	-70	477.6	235.0 - 258.8	23.8	0.63	0.06	3.50	
<i>and</i>				289.7 - 305.0	15.3	0.61	0.16	3.16	
WB04-185	60	-50	242.6	127.5 - 167.5	40.0	0.30	0.16	3.71	
WB04-186				no significant intercepts					
WB04-187				no significant intercepts					

: assay data released January 2005



# Mount Polley 2003-2005 Drilling

## Northeast Zone (9)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval		Interval Length	Copper %	Gold g/t	Silver ppm
				from	to				
WB05-188	0	-90	709.3	6.1	- 162.1	156.0	2.03	0.73	12.47
WB05-189	60	-70	483.7	202.5	- 273.8	71.3	1.09	0.20	6.24
<i>and</i>				295.7	- 344.6	48.9	1.97	0.22	11.57
WB05-190	60	-70	531.0	32.5	- 62.5	30.0	1.69	0.44	11.51
<i>and</i>				207.5	- 332.1	124.6	0.67	0.36	5.07
<i>and</i>				407.5	- 422.5	15.0	1.09	0.84	6.45
<i>and</i>				452.5	- 465.0	12.5	0.63	0.44	3.84
WB05-191	60	-70	480.7	372.5	- 377.5	5.0	0.48	0.29	3.30
WB05-192	60	-70	568.8	173.0	- 195.0	22.0	0.45	0.32	5.09
<i>and</i>				297.5	- 324.1	26.6	1.10	0.34	6.60
<i>and</i>				350.0	- 392.5	42.5	0.60	0.13	3.77
<i>and</i>				450.0	- 485.0	35.0	0.88	1.17	7.41
<i>including</i>				465.0	- 470.0	5.0	1.84	5.01	14.50
WB05-193	60	-70	563.0	7.5	- 12.5	5.0	0.33	0.63	4.20
<i>and</i>				124.8	- 127.5	2.8	1.37	1.05	10.91
WB05-194	70	-70	617.8	no significant intervals					
WB05-195	60	-70	608.4	358.6	- 386.3	27.7	0.41	0.18	3.26
<i>and</i>				405.0	- 437.5	32.5	0.52	0.34	4.12
WB05-196	60	-70	513.6	no significant intervals					
WB05-197	60	-70	754.7	372.5	- 443.0	70.5	0.65	0.07	3.57
<i>and</i>				530.8	- 542.2	11.4	1.17	0.29	8.31
<i>and</i>				553.7	- 582.5	28.8	0.39	0.96	3.31
<i>and</i>				695.0	- 710.0	15.0	0.49	0.59	3.10
WB05-198	60	-70	468.5	no significant intervals					
WB05-199	0	-90	687.9	3.7	- 20.0	16.3	0.49	0.18	4.15
<i>and</i>				30.0	- 40.0	10.0	0.37	0.14	4.58
<i>and</i>				437.5	- 448.5	11.0	0.60	0.22	4.18
<i>and</i>				618.5	- 635.0	16.5	0.46	1.04	3.17
WB05-200	60	-70	99.7	no significant intervals					
WB05-201	100	-60	642.2	no significant intervals					
WB05-202	60	-70	719.3	506.1	- 565.4	59.3	1.29	0.59	9.24
<i>and</i>				585.0	- 598.1	13.1	0.74	0.85	6.36
<i>and</i>				619.0	- 635.0	16.1	0.76	0.62	4.86
WB05-203	60	-70	541.6	182.5	- 192.5	10.0	0.43	0.34	2.65
<i>and</i>				199.3	- 236.9	37.6	0.76	0.16	4.80
WB05-204	240	-70	748.9	268.2	- 275.0	6.8	0.73	0.03	4.00
<i>and</i>				342.2	- 352.4	10.3	1.76	1.50	15.55
<i>and</i>				490.6	- 499.8	9.3	1.44	0.30	7.49
<i>and</i>				552.5	- 629.3	76.8	0.77	0.54	4.85

: assay data released April 2005

# Mount Polley 2003-2005 Drilling

## Northeast Zone (10)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from	Interval to	Interval Length	Copper %	Gold g/t	Silver ppm
WB05-205	60	-70	550.8		-	0.0			
WB05-206	60	-70	700.1	55.7	- 58.0	2.3	0.56	0.12	4.87
<i>and</i>				410.0	- 425.0	15.0	0.30	0.18	2.95
WB05-207	60	-70	608.7	455.0	- 465.0	10.0	0.41	0.02	2.38
WB05-208	60	-70	638.6	330.0	- 333.6	3.6	0.62	0.18	3.60
<i>and</i>				340.8	- 365.0	24.2	0.27	0.22	1.95
WB05-209	60	-70	636.1	287.5	- 307.3	19.8	0.39	0.02	2.64
<i>and</i>				327.5	- 334.1	6.6	0.75	0.04	6.52
<i>and</i>				356.3	- 377.9	21.6	0.56	0.04	4.93
WB05-210	240	-80	730.6	411.5	- 522.5	111.0	0.95	0.24	6.36
<i>including</i>				411.5	- 449.0	37.5	0.99	0.29	7.30
<i>including</i>				453.9	- 485.8	31.9	1.63	0.12	11.00
WB05-211	60	-70	733.35	557.5	- 572.5	15.0	0.36	0.27	2.35
<i>and</i>				645.0	- 657.5	12.5	0.25	0.64	1.41
WB05-212	60	-70	721.5	347.6	- 351.7	4.1	0.71	0.04	5.85
<i>and</i>				422.9	- 444.0	21.1	2.71	0.19	9.10
WB05-213	240	-80	675.7	467.5	- 495.3	27.8	0.71	0.64	5.78
<i>and</i>				520.9	- 547.5	26.6	0.34	0.31	3.19

: assay data released May2005

# Mount Polley 2003-2005 Drilling

## 92 Zone

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from to	Interval Length	Copper %	Gold g/t	Silver ppm
WB05-214		-90	251.8	no significant intervals				
WB05-215	240	-60	577.9	392.0 - 434.2	42.2	0.55	0.05	5.78
WB05-216	60	-70	575.2	227.5 - 252.5	25.0	0.32	0.33	2.58
WB05-217	240	-60	613.6	313.2 - 323.9	10.6	0.37	0.03	3.95
<i>and</i>				442.5 - 477.5	35.0	0.48	0.07	1.36
<i>and</i>				565.0 - 567.5	2.5	2.37	0.99	19.10
WB05-218	240	-60	599.5	315.1 - 320.7	5.6	0.38	0.02	2.53
<i>and</i>				335.0 - 340.0	5.0	0.55	0.01	2.35
WB05-219	240	-60	651.4	272.7 - 295.0	22.3	0.43	0.04	2.95
<i>and</i>				572.5 - 582.5	10.0	0.06	0.50	1.43
WB05-220	240	-60	544.7	158.4 - 228.7	70.2	0.49	0.46	4.37
<i>including</i>				158.4 - 182.5	24.1	0.81	0.48	7.27
<i>and</i>				249.3 - 265.0	15.7	0.71	0.28	3.49
<i>and</i>				280.1 - 287.5	7.4	0.50	0.14	2.34
<i>and</i>				325.0 - 332.5	7.5	0.30	0.28	1.83
WB05-221	240	-60	349.9	62.5 - 67.5	5.0	0.11	0.77	1.40
WB05-222	240	-60	188.1	no significant intervals				
WB05-223	240	-60	307.9	295.0 - 300.0	5.0	0.45	0.16	1.50
WB05-224	240	-60	285.6	230.0 - 234.9	4.9	0.49	0.02	4.90
WB05-225	240	-60	383.1	219.2 - 235.0	15.8	0.38	0.04	2.00
<i>and</i>				242.6 - 253.9	11.4	0.82	0.10	3.40
<i>and</i>				306.8 - 325.7	18.9	0.59	0.12	2.00
WB05-226	240	-60	349.6	97.5 - 108.2	10.7	0.21	0.95	1.50
<i>and</i>				117.7 - 125.0	7.3	0.17	0.79	1.50
WB05-227	240	-60	343.5	250.0 - 252.5	2.5	0.58	0.17	5.70
WB05-228	240	-60	502.0	260.9 - 271.0	10.1	0.39	0.03	2.80

: assay data released from May 2005 through January 2006

# Mount Polley 2003-2005 Drilling

## Pond Zone

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from	Interval to	Interval Length	Copper %	Gold g/t	Silver ppm
PZ05-01	270	-50	401.4	81.2	- 132.5	51.3	0.88	0.66	11.60
PZ05-02	90	-50	383.1	252.5	- 262.5	10.0	0.22	0.43	1.70
PZ05-03	270	-50	206.4	105.0	- 107.5	2.5	0.38	0.50	4.70
<i>and</i>				195.4	- 198.6	3.2	0.01	1.20	1.00
PZ05-04	90	-50	219.2	90.0	- 148.2	58.2	0.38	0.32	4.70

: assay data released July 2005 through January 2006

# Mount Polley 2003-2005 Drilling

## Southeast Zone (1)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from	Interval to	Interval Length	Copper %	Gold g/t	EqCu %
SE05-01	90	-70	167.0	12.5	- 57.5	45.0	0.36	0.59	0.82
<i>and</i>				155.0	- 167.0	12.0	0.34	0.40	0.65
<i>and</i>	90	-70	160.9	28.3	- 102.6	74.2	0.35	0.38	0.65
SE05-02				117.5	- 126.1	8.6	0.43	0.36	0.72
<i>and</i>	90	-60	218.9	19.0	- 25.0	6.0	0.23	0.44	0.57
SE05-03				43.7	- 53.1	9.3	0.20	0.34	0.46
<i>and</i>				95.0	- 142.7	47.7	0.27	0.43	0.61
SE05-04	90	-70	164.0	17.5	- 24.6	7.1	0.29	0.95	1.03
<i>and</i>				48.1	- 77.5	29.4	0.49	1.02	1.30
SE05-05	90	-70	444.4	20.0	- 57.5	37.5	0.25	0.37	0.54
<i>and</i>				145.6	- 313.2	167.6	0.24	0.48	0.62
<i>and</i>	90	-70	240.2	15.0	- 20.0	5.0	0.67	1.01	1.47
SE05-06				170.0	- 177.5	7.5	0.22	0.38	0.52
<i>and</i>				207.3	- 235.0	27.7	0.32	1.19	1.26
SE05-07	90	-70	147.5	44.1	- 62.5	18.4	0.12	0.41	0.44
<i>and</i>				80.0	- 102.5	22.5	0.20	0.42	0.53
SE05-08	90	-60	157.9	63.4	- 80.0	16.6	0.26	0.35	0.53
<i>and</i>	90	-70	270.7	24.8	- 75.0	50.2	0.18	0.32	0.43
<i>and</i>				132.5	- 197.2	64.7	0.36	0.50	0.76
SE05-09				215.0	- 232.5	17.5	0.33	0.27	0.54
<i>and</i>	90	-70	243.2	75.0	- 135.0	60.0	0.28	0.38	0.58
SE05-10				180.0	- 205.0	25.0	0.51	0.92	1.23
SE05-11	90	-70	304.2	20.0	- 40.0	20.0	0.08	1.11	0.97
<i>and</i>				107.5	- 132.5	25.0	0.21	0.44	0.56
<i>and</i>				282.5	- 292.6	10.1	0.31	0.33	0.57
SE05-12	90	-70	167.0	12.5	- 57.5	45.0	0.36	0.59	0.82
<i>and</i>				155.0	- 167.0	12.0	0.34	0.40	0.65
SE05-13	90	-70	160.9	28.3	- 102.6	74.2	0.35	0.38	0.65
<i>and</i>				117.5	- 126.1	8.6	0.43	0.36	0.72
<i>and</i>	90	-60	218.9	19.0	- 25.0	6.0	0.23	0.44	0.57

: assay data released April 2005

# Mount Polley 2003-2005 Drilling

## Southeast Zone (2)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from	Interval to	Interval Length	Copper %	Gold g/t	EqCu %
SE05-14	90	-70	507.8	90.0	- 114.4	24.4	0.13	0.64	0.63
<i>and</i>				129.1	- 253.7	124.6	0.25	0.50	0.64
<i>and</i>				281.3	- 462.5	181.2	0.15	0.59	0.62
<i>including</i>				327.5	- 353.0	25.5	0.21	1.52	1.41
SE05-15	90	-70	615.1	90.0	- 106.5	16.5	0.21	0.44	0.55
<i>and</i>				118.9	- 174.1	55.2	0.20	0.49	0.59
<i>and</i>				195.9	- 232.5	36.6	0.30	0.76	0.90
<i>and</i>				252.2	- 298.6	46.4	0.26	0.87	0.94
<i>and</i>				352.2	- 420.9	68.7	0.21	0.38	0.50
<i>and</i>				435.0	- 565.0	130.0	0.24	0.41	0.56
<i>including</i>				548.7	- 565.0	16.3	0.28	0.54	0.70
<i>and</i>				590.0	- 610.0	20.0	0.22	0.28	0.44
SE05-16	90	-70	435.0	67.0	- 80.0	13.0	0.22	0.39	0.53
<i>and</i>				187.5	- 205.0	17.5	0.14	0.46	0.50
SE05-17	90	-70	499.3	45.0	- 57.5	12.5	0.06	0.58	0.51
<i>and</i>				67.2	- 102.5	35.4	0.17	0.43	0.51
<i>and</i>				115.4	- 147.3	31.9	0.21	0.37	0.50
<i>and</i>				166.1	- 205.0	38.9	0.29	0.58	0.75
<i>and</i>				218.5	- 270.0	51.6	0.26	0.56	0.70
SE05-18	90	-70	376.7	3.1	- 7.5	4.5	0.30	0.34	0.56
<i>and</i>				205.0	- 213.6	8.6	0.43	0.62	0.91
<i>including</i>				180.0	- 213.6	33.6	0.20	0.32	0.45
<i>and</i>				239.6	- 269.1	29.5	0.29	0.34	0.56
<i>and</i>				317.0	- 322.5	5.5	0.63	0.48	1.01
SE05-19	90	-70	432.2	23.1	- 37.1	14.0	0.14	0.74	0.72
<i>and</i>				87.5	- 138.4	50.9	0.25	0.54	0.67
<i>including</i>				97.5	- 120.0	22.5	0.39	0.82	1.03
<i>and</i>				187.5	- 204.7	17.2	0.32	0.76	0.91
<i>and</i>				227.5	- 250.9	23.4	0.15	0.29	0.38
<i>and</i>				282.6	- 362.5	79.9	0.74	1.02	1.54
<i>including</i>				331.0	- 346.1	15.1	1.77	2.91	4.06
SE05-20	90	-60	294.7	52.0	- 60.0	8.0	0.24	0.42	0.57
<i>and</i>				102.5	- 122.5	20.0	0.44	0.70	1.00
<i>and</i>				232.5	- 237.5	5.0	0.06	1.05	0.89
SE05-21	90	-60	206.4	85.0	- 127.5	42.5	0.14	0.44	0.49
SE05-22	90	-70	401.7	10.0	- 28.0	18.0	0.31	0.44	0.66
<i>and</i>				67.5	- 92.5	25.0	0.16	0.31	0.41
SE05-23	90	-70	252.1	27.5	- 32.5	5.0	0.40	0.38	0.70
<i>and</i>				185.0	- 197.4	12.4	0.21	0.27	0.42
SE05-24	90	-60	377.0	63.1	- 84.7	21.6	0.16	0.26	0.36
<i>and</i>				93.0	- 143.0	50.0	0.18	0.34	0.45
<i>and</i>				158.7	- 172.5	13.8	0.31	0.47	0.68
<i>and</i>				261.3	- 277.5	16.2	0.23	0.32	0.48
<i>and</i>				365.0	- 377.0	12.0	0.05	0.84	0.71

: assay data released May 2005

# Mount Polley 2003-2005 Drilling

## Southeast Zone (3)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from	Interval to	Interval Length	Copper %	Gold g/t	EqCu %
SE05-25	90	-70	371.3	62.5	70.0	7.5	0.17	0.35	0.45
<i>and</i>				125.0	157.7	32.7	0.19	0.38	0.49
<i>and</i>				188.0	250.0	62.0	0.29	0.38	0.59
<i>and</i>				331.6	345.0	13.4	0.10	0.30	0.34
SE05-26	90	-70	185.0	135.0	140.0	5.0	0.24	0.26	0.44
SE05-27	90	-70	215.5	25.0	38.0	13.0	0.37	0.66	0.89
<i>and</i>				92.5	102.5	10.0	0.10	0.35	0.38
SE05-28	90	-70	264.3	13.8	108.3	94.4	0.40	0.74	0.99
<i>including</i>				13.8	30.0	16.2	0.79	1.47	1.95
<i>and</i>				144.5	175.0	30.5	0.12	0.33	0.38
<i>and</i>				195.0	200.0	5.0	0.46	0.89	1.16
<i>and</i>				240.0	245.0	5.0	0.15	0.64	0.66
SE05-29	90	-70	252.1	no significant intervals					
SE05-30	90	-70	456.6	35.0	40.0	5.0	0.19	0.68	0.73
<i>and</i>				62.5	67.5	5.0	0.12	0.44	0.46
<i>and</i>				102.5	107.5	5.0	0.28	0.68	0.81
<i>and</i>				167.5	190.0	22.5	0.33	0.81	0.96
SE05-31	90	-70	492.9	57.5	62.5	5.0	0.44	1.49	1.61
<i>and</i>				75.0	80.1	5.1	0.24	0.33	0.50
<i>and</i>				92.5	132.5	40.0	0.21	0.72	0.77
<i>and</i>				150.0	167.5	17.5	0.23	0.72	0.80
<i>and</i>				179.6	185.0	5.4	0.24	0.68	0.77
<i>and</i>				207.5	227.5	20.0	0.47	0.83	1.12
<i>and</i>				265.0	293.9	28.9	0.20	0.28	0.42
<i>and</i>				367.5	375.0	7.5	1.43	2.11	3.09
<i>and</i>				467.5	474.6	7.1	0.33	0.43	0.66
SE05-32	90	-70	215.5	no significant intervals					
SE05-33	90	-70	282.6	222.5	255.0	32.5	0.08	0.41	0.41
<i>including</i>				222.5	237.5	15.0	0.17	0.51	0.57
SE05-34	90	-70	658.0	24.0	37.7	13.7	0.28	0.49	0.67
<i>and</i>				49.8	55.0	5.2	0.16	0.41	0.48
<i>and</i>				62.5	67.5	5.0	0.19	0.31	0.43
<i>and</i>				97.5	100.0	2.5	0.40	0.57	0.85
<i>and</i>				124.4	132.5	8.1	0.24	0.49	0.62
SE05-35	90	-60	255.1	10.0	47.5	37.5	0.21	0.54	0.64
<i>and</i>				233.3	237.5	4.2	0.26	0.34	0.52
SE05-36	90	-70	642.2	27.5	39.5	12.0	0.11	0.51	0.51
<i>and</i>				173.0	351.4	178.4	0.23	0.53	0.65
<i>and</i>				377.5	607.5	230.0	0.23	0.40	0.55
SE05-37	90	-70	289.0	no significant intervals					
SE05-38	90	-70	139.3	157.5	172.0	14.5	0.16	0.33	0.42
SE05-39	90	-70	298.1	155.0	165.0	10.0	0.15	0.47	0.52
<i>and</i>				177.2	208.8	31.6	0.26	0.43	0.59
<i>and</i>				225.5	272.5	47.0	0.62	0.86	1.30

: assay data released May 2005 through July 2005

# Mount Polley 2003-2005 Drilling

## Southeast Zone (4)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from to	Interval Length	Copper %	Gold g/t	EqCu %
SE05-40	90	-70	270.4	55.0 - 75.0	20.0	0.11	0.39	0.42
<i>and</i>				85.0 - 112.5	27.5	0.15	0.43	0.49
<i>and</i>				125.0 - 142.8	17.8	0.17	0.40	0.48
<i>and</i>				265.0 - 270.4	5.4	0.05	0.61	0.53
SE05-41	90	-70	432.2	40.2 - 47.5	7.4	0.16	0.70	0.71
SE05-42	90	-70	416.7	370.0 - 390.0	20.0	0.03	0.99	0.81
SE05-43	90	-70	422.8	152.5 - 158.1	5.6	0.17	1.26	1.16
<i>and</i>				187.5 - 205.0	17.5	0.29	0.77	0.90
SE05-44	90	-70	289.0	122.5 - 135.0	12.5	0.37	0.66	0.89
<i>and</i>				155.0 - 160.0	5.0	0.26	0.67	0.78
<i>and</i>				177.5 - 185.0	7.5	0.13	1.94	1.66
<i>and</i>				212.5 - 257.9	45.4	0.18	0.50	0.57
SE05-45	90	-60	203.3	82.5 - 95.0	12.5	0.23	0.47	0.60
				127.5 - 134.7	7.2	0.19	0.45	0.55
SE05-46	90	-70	191.1	145.0 - 160.0	15.0	0.23	0.31	0.47
				177.5 - 185.0	7.5	0.23	0.40	0.55

: assay data released July 2005

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from to	Interval Length	Copper %	Gold g/t	EqCu %
SE05-47	90	-70	200.3	no significant intervals				
SE05-48	90	-70	233.8	90.9 - 110.4	19.5	0.22	0.26	0.42
SE05-49	270	-60	300.8	32.5 - 43.0	10.5	0.35	0.64	0.85
<i>and</i>				129.8 - 133.9	4.1	0.22	0.83	0.88
<i>and</i>				176.6 - 276.9	100.4	0.42	0.80	1.04
including				220.0 - 252.5	32.5	0.75	1.43	1.87
SE05-50	90	-70	310.0	170.0 - 175.0	5.0	0.26	1.43	1.39
<i>and</i>				180.3 - 215.8	35.5	0.33	0.32	0.58
SE05-51	90	-70	194.8	85.0 - 91.4	6.4	0.13	0.42	0.46
<i>and</i>				112.5 - 117.5	5.0	0.35	0.55	0.79
SE05-52	90	-70	207.0	no significant intervals				
SE05-53	90	-70	197.8	125.8 - 142.5	16.7	0.20	1.05	1.03
SE05-54	210	-50	216.7	no significant intervals				

: assay data released January 2006



# Mount Polley 2003-2005 Drilling

## Boundary Zone

Drill Hole #	Azimuth (°)	Dip (°)	Total Length (m)	Metre Interval		Interval Length (m)	Copper %	Gold g/t	Silver ppm
				from (m)	to (m)				
ND04-01		-90	252.1	4.3	- 17.6	13.4	0.76	0.51	6.24
				53.3	- 110.8	57.5	1.59	1.91	7.71
ND04-02	60	-50	240.5	6.1	- 57.5	51.4	0.30	0.45	2.04
				77.5	- 147.5	70.0	0.29	0.61	2.42
ND04-03	30	-50	273.1	4.3	- 19.3	15.0	0.42	0.73	3.13
ND04-04	90	-60	306.6	8.8	- 13.9	5.0	0.35	0.57	2.75
				232.5	- 250.5	18.0	0.42	0.41	2.00

*: assay data released August 2004*

# Mount Polley 2003-2005 Drilling

## Springer Zone (1)

Drill Hole #	Total Length (m)	Metre Interval	Interval Length	Copper %	Gold g/t
SD03-01	481.3	3.7 - 470.0	466.3	0.49	0.36
<i>including</i>		202.5 - 470.0	267.5	0.61	0.49
<i>and</i>		295.0 - 375.3	80.3	0.94	0.64
<i>and</i>		320.0 - 372.5	52.5	1.14	0.81
SD03-02	675.1	160.0 - 647.5	487.5	0.31	0.26
<i>including</i>		255.0 - 321.6	66.6	0.44	0.38
SD03-03	675.1	150.2 - 665.0	514.8	0.25	0.36
<i>including</i>		150.2 - 575.0	424.8	0.26	0.38
<i>and</i>		452.2 - 575.0	122.8	0.46	0.62
SD03-04	769.3	82.5 - 625.0	542.5	0.28	0.24
<i>including</i>		217.5 - 330.0	112.5	0.47	0.29
SD03-05	639.5	187.5 - 532.5	345.0	0.40	0.24
<i>including</i>		395.0 - 532.5	137.5	0.60	0.32
SD03-06	739.8	10.0 - 237.5	227.5	0.44	0.42
<i>and</i>		379.7 - 601.8	221.4	0.37	0.29
SD04-07	648.3	20.4 - 41.8	21.5	0.43	0.48
<i>and</i>		66.2 - 112.5	46.3	0.43	0.48
SD04-08	648.3	3.4 - 177.5	174.2	0.32	0.30
<i>and</i>		217.5 - 382.5	165.0	0.32	0.35
SD04-09	669.0	3.1 - 287.5	284.5	0.33	0.25
SD04-10	617.2	115.0 - 155.0	40.0	0.19	0.29
<i>and</i>		175.0 - 209.6	34.6	0.30	0.31
<i>and</i>		332.5 - 380.0	47.5	0.36	0.33
<i>and</i>		420.0 - 450.0	30.0	0.83	0.95
SD04-11	1004.0	282.5 - 555.7	273.2	0.72	0.35
<i>and</i>		467.5 - 541.3	73.8	1.62	0.62
SD04-12	544.7	142.5 - 172.5	30.0	0.28	0.45
SD04-13	785.2	32.5 - 42.5	10.0	0.46	0.14
<i>and</i>		430.0 - 621.5	191.5	0.45	0.45
<i>including</i>		440.0 - 499.5	59.5	0.95	0.84
<i>and</i>		645.9 - 702.5	56.6	0.30	0.59
SD04-14	961.5	260.0 - 780.0	520.0	0.37	0.38
<i>including</i>		460.0 - 517.5	57.5	0.55	0.55
SD04-15	730.6	305.0 - 354.4	49.4	0.34	0.28
SD04-16	730.6	325.0 - 595.0	270	0.56	0.58
<i>including</i>		500.0 - 592.8	92.8	1.11	1.15
<i>including</i>		557.4 - 574.4	17.0	2.30	2.70

: assay data released November 2003 through August 2004

# Mount Polley 2003-2005 Drilling

## Bell Pit (1)

Drill Hole #	Azimuth	Dip	Length (m)	Metre Interval		Interval Length	Copper %	Gold g/t	
				from	to				
BD04-01	270°	-55°	150.9	51.9	-	95.0	43.1	0.35	0.27
BD04-02	270°	-75°	385.9	70.0	-	130.0	60.0	0.35	0.23
<i>and</i>				177.5	-	338.5	161.0	0.35	0.30
BD04-03	270°	-56°	160.3	18.1	-	88.2	70.1	0.26	0.18
<i>including</i>				30.0	-	65.5	35.5	0.31	0.20
BD04-04	270°	-75°	181.4	71.5	-	130.0	58.5	0.40	0.29
BD04-05	270°	-45°	89.9	3.1	-	71.7	68.6	0.86	0.67
<i>including</i>				24.9	-	71.7	46.8	1.15	0.86
BD04-06	270°	-75°	200.0	3.1	-	68.9	65.8	0.28	0.22
<i>including</i>				3.1	-	19.6	16.5	0.40	0.36
<i>and</i>				93.7	-	135.0	41.3	0.40	0.34
BD04-07	270°	-61°	114.6	6.1	-	87.6	81.5	0.47	0.38
<i>including</i>				71.3	-	82.5	11.2	1.36	1.09
BD04-08	270°	-80°	196.9	6.1	-	35.0	28.9	0.59	0.45
<i>and</i>				48.7	-	150.0	101.3	0.39	0.39
BD04-09	270°	-75°	349.0	3.1	-	20.0	16.9	0.31	0.10
<i>and</i>				228.2	-	255.0	26.8	0.30	0.22
BD04-10	270°	-52°	269.8	70.0	-	100.0	30.0	0.26	0.11
<i>and</i>				145.0	-	156.4	11.4	0.36	0.21
BD04-11	270°	-45°	169.2	10.8	-	51.0	40.2	0.21	0.29
<i>and</i>				67.9	-	118.5	50.6	0.29	0.39
BD04-12	270°	-70°	221.6	80.0	-	157.3	77.3	0.37	0.63
<i>and</i>				171.2	-	208.3	37.1	0.75	1.12
BD04-13	270°	-60°	245.4	54.6	-	65.0	10.4	0.34	0.31
<i>and</i>				109.9	-	225.0	115.1	0.41	0.69
BD04-14	270°	-60°	242.9	95.0	-	146.7	51.7	0.32	0.35
<i>and</i>				162.9	-	198.7	35.8	0.40	0.42
BD04-15	0°	-50°	364.9	112.5	-	174.6	62.1	0.38	0.67
<i>and</i>				198.6	-	227.5	28.9	0.29	0.38
<i>and</i>				262.5	-	288.9	26.4	0.29	0.31
BD04-16	270°	-55°	126.5	27.5	-	70.0	42.5	0.30	0.21
BD04-17	170	-50°	245.4	3.7	-	222.5	218.9	0.50	0.43
BD04-18	270°	-50°	242.9	171.0	-	224.2	53.1	0.31	0.49
BD04-19	270°	-45°	242.9	132.5	-	188.7	56.2	0.33	0.55
BD04-20	270°	-50°	238.7	20.0	-	35.4	15.4	0.41	0.32
<i>and</i>				107.5	-	120.0	12.5	0.41	0.28
BD04-21	270°	-60°	197.6	131.4	-	187.2	55.8	0.27	0.39
BD04-22	270°	-60°	245.4	137.5	-	157.5	20.0	0.40	0.27
BD04-23	270°	-50°	197.2	72.5	-	100.0	27.5	0.34	0.31
<i>and</i>				124.3	-	172.5	48.2	0.48	0.49
BD04-24	270°	-55°	193.2	127.5	-	165.0	37.5	0.47	0.36
BD04-25	270°	-45°	264.0	175.0	-	233.3	58.3	0.27	0.45
BD04-26	270°	-50°	224.0	106.1	-	168.6	62.5	0.91	0.86
<i>including</i>				140.0	-	168.6	28.6	1.61	1.60
BD04-27	315°	-50°	175.9	85.0	-	110.0	25.0	0.35	0.45
BD04-28	270°	-50°	181.4	45.0	-	55.0	10.0	0.27	0.35
<i>and</i>				137.5	-	150.0	12.5	0.29	0.39
BD04-29	270°	-50°	166.7	87.5	-	127.5	40.0	0.31	0.58
BD04-30	320°	-55°	167.5	125.0	-	158.5	33.5	0.27	0.41

: assay data released February 2004 through April 2004